


UNION COUNTY
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was never set.



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

See Map of Survey Number 015-1992.

Description of monument and accessories I established to perpetuate the original location of this corner:

At position determined by survey, I set a 5/8" x 30" rebar with aluminum cap marked as shown, 26 inches in the ground, from which:

A 8" Ponderosa Pine bears S60°E, 19.15 feet, marked X BT


A 16" Ponderosa Pine bears S79°W, 9.27 feet, marked C-N 1/16 S 10 BT

Set steel fence post 1 foot south.

There is a fence corner 91 feet south and 100 feet east, fences running N-S-E.

I hereby certify that the above corner point was perpetuated as hereon described on May 15, 1992.

Whitness:
Pete Crabtree



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 20° East magnetic declination. The distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

**UNION COUNTY
SURVEYOR**

Date Received 6/10/92
Date Filed 6/20/92
By My Black
File No. 030-1992R