

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Section corner common to Sections 12 & 13, T2N, R39E and Sections 7 & 18, T2N, R40E, W.M., Union County, Oregon

Original corner established in 1864 by T. Davenport under contract No. 102 approved 1/12/1864. He set a post for the section corner common to sections 12, 13, 7 & 18 from which:

- A Pine 36" in diameter bears N69°E, 60 Lks. distance.
- A Pine 20" in diameter bears N72°W, 50 Lks. distance.
- A Pine 24" in diameter bears S58°W, 14 Lks. distance.
- A Pine 9" in diameter bears S67°E, 208 Lks. distance.

Description of corner evidence found:

No original corner evidence or references were found.


REGISTERED PROFESSIONAL LAND SURVEYOR

B. A. Sutton
OREGON
JULY 13, 1979
B. A. SUTTON
1848

RENEWAL 6/30/98

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2-1/2"x30" aluminum capped aluminum pipe marked: at the proportioned location between the Witness Corner for the 1/4 corner to the South and the original location of the 1/4 corner to the North.



I established the following references:

- A 13" Ponderosa Pine bears N43°E, 38.3' blazed & scribed; (T2NR40ES7BT)
- A 9" Ponderosa Pine bears S17°30'E, 4.4' blazed & scribed; (T2NR40ES18BT)
- A 14" Ponderosa Pine bears S44°45'W, 77.0' blazed & scribed; (T2NR39ES13BT)
- An 11" Ponderosa Pine bears N80°30'W, 44.0' blazed & scribed; (T2NR39ES12BT)

Office of the _____ County Surveyor _____ County of _____ Union _____

State of Oregon, I hereby certify that the within instrument was filed in this office

for record on the _____ day of _____, 19 _____

_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received 9/16/96

Date Filed 10/05/96

By *Alyson T. Blawie*

File No. 097-1996