CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner not previously established

T2N R40 EK-13



DESCRIPTION OF CORNER EVIDENCE FOUND:

None

SEE SURVEY NUMBER 029-2022

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At position by survey, I set a 5/8" x 30" iron pin, 27" in the ground, with 2 1/2" aluminum cap marked as shown and in a 2 ft. diam. collar of stone, from which:

NEW BEARING OBJECTS:

A 5/8" x 30" iron pin bears NORTH a dist. of 25.00 ft., marked "N RP BGB SURVEY MARKER" A 5/8" x 30" iron pin bears South 43°06' East a dist. of 40.00 ft., marked "SE RP BGB SURVEY MARKER"

Set steel fence post approx. 0.5 ft. North

Fence corner to North and Southeasterly bearing fencelines bears approx. 40 ft. Southeast

I hereby certify that the corner was monumented on September 7, 2022.

Witness: Dan S. Drum, Kyle A. Tucker

S16 S15

OPLS 83571
2022

REGISTERED
PROFESSIONAL
LAND SURWEYOR

OREGON June 2, 2010 JEFFREY S. HSU 83571

Renewal Date: June 30, 2023

I used a Leica GS18 RTK in the establishment of the new accessories. Basis of Bearing is as per Survey Number 029-2022. Distances and bearings are to the centers of the aluminum caps.

UNION COUNTY
SURVEYOR

Date Received 9 14 27

Date Filed 9 14 177

File Number 433 20778