

UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

CORNER NOT ORIGINALLY SET

DESCRIPTION OF CORNER EVIDENCE FOUND:

NONE

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the surveyed position, I set a 2½"x30" aluminum pipe with cap 26" in the ground, from which:

NEW BEARING OBJECTS:

An 18" diameter Douglas Fir bears N 29° E, a distance of 45.98 feet, marked X BT.

A 20" diameter Douglas Fir bears S 60° E, a distance of 15.67 feet, marked C ¼ S 18 BT.


A 20" diameter Ponderosa Pine bears S 65°W, a distance of 47.67 feet, marked C ¼ S 18 BT.

A 9" diameter Douglas Fir bears N 43°W, a distance of 61.31 feet, marked C ¼ S 18 BT.

I hereby certify that the corner was monumented on March 25, 1996.

Witness: Mark Durbin, Jeff Madsen

T 2 N R 40 E L-03



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Gregory T. Blackman

OREGON
JULY 13, 1973

GREGORY T. BLACKMAN
991

Renewal Date: December, 31 1999

BAGETT - GRIFFITH & BLACKMAN

T2N R40E

C 1/4

+

S 18

1998

OPLS 991

**UNION COUNTY
SURVEYOR**

Date Received 5/15/98

Date Filed 8/29/98

Filed By R. ROBINSON, DEPUTY

File Number 043-1998R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 17° East declination, The distances are to a 60d spike driven into the right side of the root crown of the new bearing trees. A brass washer marked OPLS 991 is attached to the BT blaze of the new trees.