

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner was established by Rufus Moore under GLO Contract No. 382, dated March 23, 1881.

Surveyor General record states:

Set post for 1/4 sec. cor. from which:

A pine 18 ins. diam. bears S. 80° E., 14 lks. dist.
A pine 12 ins. diam. bears N. 51° W., 33 lks. dist.



Description of corner evidence found:

Found a 4 ft. high stump 18-ins. diam at record bearing and distance for Sec. 16 BT (N. 51° W., 33 lks. dist.) This BT was part of a N-S running fence; old barbed wire still protruding from stump. The scribing "/4" is visible.

No evidence of the other original BT.

UNION COUNTY SURVEYOR

Date Received 12-31-85

Date Filed 12-31-85

By G. LANGRIZ DEPUTY

File No. 178-85 R


Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 1 1/2-inch O.D. iron pipe with 2 1/2-inch brass cap in small stone mound at record bearing and distance. Pipe is 30 inches long, set 26 inches in the ground.

Set a steel fence post alongside with USFS Sign No. 54-4 attached.

Attached a USFS BT tag and 54-4 tag to the BT stump.

Monument is marked thus:



I certify that the above described corner monument was properly reestablished under my supervision on July 1, 1985 by Tom Fisk and Chris Mahoney.

REGISTERED PROFESSIONAL LAND SURVEYOR

James D. Hanley

REGISTERED
SEPTEMBER 1977
JAMES D. HANLEY
1206

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL) (DEPUTY)