

430

UNION COUNTY
SURVEYOR

T. 2 S., R. 34 E., Willamette Meridian, Oregon

Date Received 3/8/13
Date Filed 3/8/13
By [Signature] DEPUTY
File No. 216-2013R

The mean magnetic declination is 19° East.

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

(Restoring the survey by James P. Currin and James E. Noland
in 1887, and the resurvey by Lincoln E. Wilkes in 1917)

Beginning at the 63 Mile Corner on the S. bdy. of the Umatilla
Indian Reservation, perpetuated and recorded by Barry B. Barbour,
Registered Land Surveyor No. 1051, in 1980, monumented with an
iron post, 2 ins. diam., firmly set, protruding 12 ins. above
ground, with brass cap mkd.

T 2 S R 34 E
UIR
63M
1917

from which the remains of the original bearing trees

A ponderosa pine snag, 40 ins. diam., bears S. 83½° E.,
29 lks. dist., with illegible scribe marks on upper
partially healed blaze, and BT on lower partially
healed blaze. (Record, 28 lks.)

A ponderosa pine, 39 ins. diam., bears N. 43° W.,
54½ lks. dist., with illegible scribe marks on
partially healed blaze. (Record, N. 44½° W., 53 lks.)

and a bearing tree mkd. by Barbour

A ponderosa pine, 18 ins. diam., bears S. 1½° E.,
87 lks. dist., with scribe marks UIR MP 63 BT
on partially healed blaze.

Raise a mound of stone, 3 ft. base, to top, around iron post.

The corner is located on SW. slope in barbed wire fence, 3
strands, bears generally E. and W.

N. 89° 47' 00" W., on the 64th mile.

Descend over SW. slope, through timber and light undergrowth.

Retracement-Resurvey of the East Boundary
Original Umatilla Indian Reservation

Chains

of secs. 25 and 36, the position of which is determined from original bearing tree, as follows:

A fir, 10 ins. diam., bears S.70°E., 9 lks. dist., marked U I R B T.

The $\frac{1}{2}$ cor. bet. secs. 35 and 36 bears N.2°10'E., 3.92 chs. dist.

8.05 The 62 $\frac{1}{2}$ Mile Cor., which is a decayed post. In its place Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for 62 $\frac{1}{2}$ Mile Cor., with brass cap marked

T2S R34E
UIR / 62 $\frac{1}{2}$ M
1917

from which

A pine, 22 ins. diam., bears S.17°E., 24 $\frac{1}{2}$ lks. dist., blazes healed over and unopened.

A fir, 20 ins. diam., bears N.31°W., 34 lks. dist., blazes healed over and unopened.

I remark these trees U R 62 $\frac{1}{2}$ M B T.

Thence

N.20°18'E., continuing my measurements.

15.65 "Daly" wagon road, bears NW. and SE.

23.05 Leave rolling land and descend 400 ft., closely following summit of low ridge.

47.86 The 62 Mile Cor., heretofore described.

Land, mountainous and bench.

Soil, light loam, shallow, on basalt bedrock; 2nd rate.

Timber, pine, fir and balsam.

Undergrowth, fir, balsam and willow.

Retracement-Resurvey of the South Boundary
Original Umatilla Indian Reservation

From the SE. angle cor. of the Umatilla Indian Reservation West, retracing the 63rd Mile.

32.30 Fall 17 lks. N. of the 63 Mile Cor., the position of which being determined from the original bearing trees.

UNION COUNTY SURVEYOR

Date Received 3/11/13

Date Filed 3/11/13

By J. L. DEPTON

File No. 263-2013R

Retracement-Resurvey of the South Boundary
Original Umatilla Indian Reservation

Chains

At exact cor. point
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for 63 Mile Cor., with brass cap marked

T2SR34E
UIR
63M
1917

from which

A pine, 48 ins. diam., bears N.44°30'W., 53 lks.
dist., marked in bark 63 M U R B T (old B.T.)

A pine, 42 ins. diam., bears S.83°30'E., 28 lks. dist.,
marked in bark 63 M U R B T (old B.T.)

I remove these marks and cut the marks in the wood.

Thence

N.89°42'E., resurveying 63rd Mile

Over mountainous land, through heavy timber and medium
undergrowth.

Ascend 250 ft. to

24.00 Top of ascent, bears N. and SE.; enter rolling land.

32.30 The SE. angle cor. of Umatilla Indian Reservation.

Land, mountainous and bench.

Soil, light loam, shallow, on basalt bedrock; 2nd rate.

Timber, pine, fir and balsam.

Undergrowth, fir, balsam and willow.

From the 63 Mile Cor.

West, retracing the 64th Mile

40.26 Pass 5 lks. S. of the 63 $\frac{1}{2}$ Mile Cor. hereinafter described.

80.39 Fall 18 lks. S. of the 64 Mile Cor., which is a basalt
stone, 16x14x6 ins., marked 64 M on W. face, set in a
small mound of stone.

At a point 1 lk. W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the
ground to bedrock, in a mound of stone, 5 ft. base, 1 $\frac{1}{2}$
ft. high, for witness cor. to the 64 Mile Cor., with
brass cap marked

UNION COUNTY
SURVEYOR

Date Received 3/11/13

Date Filed 3/11/13

By [Signature] DEPUTY

File No. 263-2013R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. MP 63


History of original corner establishment:

Corner was recovered by L. Wilkes, survey group No. 38, during October, 1917. Surveyors General's notes state: "Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for 63 Mile Cor., with brass cap marked:

T2SR34E
ULR
63M

1917

from which: A pine, 48 ins. diam. bears N44°30'W., 53 lks. dist. marked in bark 63 MUR BT (Old B.T.). A pine, 42 ins. diam. bears S83°30'E., 28 lks. dist. marked in bark 63 MUR BT (Old B.T.)."



Description of corner evidence found:

Found 2" iron pipe with brass cap projecting 14" above the ground. From which: A 48" pine bears N43°W, 36.5 ft. visible scribing. A dead 40" pine bears S86°E, 20.1 ft. scribed M63 ULR BT.

Marked:
T2S R34E
ULR
M63
1917

Description of monument and accessories I established to perpetuate the original location of this corner:

From which I add: An 18" pine bears S01°E, 57.4 ft. scribed ULR MP63 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped P1S 1051 on new BT. Placed 54-2 and 54-4 on steel fence post 5' east of the corner.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Douglas Moser

October 30, 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour
OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

UNION COUNTY SURVEYOR

Date Received _____
Date Filed _____
By _____
NARRATIVE DRAWER 1/3
File No. _____

REFER TO SURVEY 10-81

Office of.....County Surveyor..... County of Union.....
State of Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 30th day of January....., 1981.

..... by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

UNION COUNTY SURVEYOR

☆ GPO-798-276
Date Received 3/12/13
Date Filed 3/12/13
By J. M. L. DEPUTY
File No. 283-2013R