

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

35.810 The 64½ Mile Corner on the S. bdy. of the Umatilla Indian Reservation, monumented with the original basalt stone, 16 x 12 x 8 ins. (record, 16 x 14 x 4 ins.), firmly set, protruding 8 ins. above ground, mkd. ½ M on E. face, from which the remains of the original bearing trees:

A ponderosa pine stump, 48 ins. diam., bears
S. 43° W., 44 lks. dist., no marks visible.

A ponderosa pine stump, 35 ins. diam., bears
N. 48° W., 102 lks. dist., no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 2 S R 34 E
UIR
64½M
S 34
1988

from which new bearing trees

A fir, 12 ins. diam., bears N. 13° E., 11½ lks. dist.,
mkd. 64½M UIR BT.

A fir, 13 ins. diam., bears S. 27° E., 21 lks. dist.,
mkd. 64½M UIR BT.

Deposit a white "DEEP-1" magnetic marker at the base and the original stone alongside the stainless steel post.

From this point, the witness cor. to the 64½ Mile Corner, established by Wilkes in 1917 and perpetuated and recorded by Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980, bears West, 0.010 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, protruding 12 ins. above ground, in a collar of stone, with brass cap mkd. T2S R34E UIR 64½M WC 1917, from which the bearing trees mkd. by Barbour:

A larch, 14 ins. diam., bears N. 64° E., 51 lks. dist.,
with scribe marks UIR MP 64½ WC BT and a nail and
washer at base of partially healed blaze.

A ponderosa pine, 15 ins. diam., bears S. 77¾° W.,
93½ lks. dist., with scribe marks UIR MP 64½ WC BT
and a nail and washer at base of partially healed blaze.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By J. L. DEERY

File No. 219-2013R

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CLAIMS

Bury the iron post in place.

The corner is located on NE. slope, in timber and light undergrowth.

N. $89^{\circ} 34' 30''$ W., beginning new measurement.

2.95 Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.

4.020 The closing cor. of secs. 33 and 34, for the south side of the Reservation boundary, established and recorded by Harry B. Barbour, Registered Land Surveyor No. 1051, in 1980, and is accepted as the corner, monumented with an iron post, 2 ins. diam., firmly set, protruding 20 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E

UIR

S 33 | S 34

C | C

OR PLS 1051

1980

from which a bearing tree mkd. by Barbour

A ponderosa pine, 16 ins. diam., bears S. 61° E.,
341 lks. dist., with scribe marks T2S R34E S34 CC BT
and a nail and washer at base of partially healed blaze.

From this point, the original closing cor. of secs. 33 and 34 established by Wilkes in 1917, bears S. $2^{\circ} 29' 00''$ E., 0.075 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, protruding 24 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T2S R34E UIR S33 S34 CC 1917, from which the remains of a bearing tree mkd. by Wilkes:

A root hole, bears S. $56\frac{1}{2}^{\circ}$ W., 234 lks. dist., with
ponderosa pine, 8 ins. diam., lying alongside, with
scribe marks CC T2S R34E S3 BT on partially healed blaze.

Mark the brass cap AM and bury the iron post in place.

N. $89^{\circ} 50' 30''$ W., beginning new measurement.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 219-2013R

Retracement-Resurvey of the South Boundary

7R1

Original Umatilla Indian Reservation

Chains
40.01

Intersect 64 $\frac{1}{2}$ Mile Cor., which is a basalt stone, 16x14x4 ins., set 12 ins. in the ground, marked $\frac{1}{2}$ M on E. and U R on W. face; from which

A pine, 48 ins. diam., bears S.43°W., 44 lks. dist., marked U I R 64 $\frac{1}{2}$ M B T.

A pine, 20 ins. diam., bears N.48°W., 102 lks. dist., blazes healed over, not opened.

At a point 1 lk. W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to the 64 $\frac{1}{2}$ Mile Cor., with brass cap marked

T2S R34E
UIR
64 $\frac{1}{2}$ WC
1917

Thence

N.89°51'E., resurveying east half of 65th Mile.

Over heavily rolling land, following a fence.

Cross a draw, course SE. (exact distance not noted, about 45.00 chs.)

56.66 Cor. of fence, extending N. and W.

80.87 The 64 Mile Cor., heretofore described.

Land, high, rolling and mountainous.

Soil, shallow; 2nd rate.

Timber, yellow and lodgepole pine and fir.

Undergrowth, lodgepole pine and fir.

From the 65 Mile Cor.

West, retracing the 66th Mile.

Pass 10 lks. N. of the 65 $\frac{1}{2}$ Mile Cor., hereinafter described.

79.45 Fall 20 lks. S. of the 66 Mile Cor., which is an old post, much decayed, in place of which I

Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground with mound of stone, 3 ft. base, 1 ft. high,

raised around post, with brass cap marked

T2SR34E
UIR
66M
1917

UNION COUNTY
SURVEYOR

Date Received 3/11/13

Date Filed 3/11/13

By J. J. L. DEPUTY

File No. 266-2013R