

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

~~19.30 Creek, dry, 2 lks. wide, drains generally S., asc. E. slope.
20.695 Point for the closing cor. on the N. and S. center line of the
SE¼ of sec. 34, for that portion of the section north of the
Reservation boundary, hereinafter described.~~

35.380 The true point for the 64 Mile Corner on the S. bdy. of the
Umatilla Indian Reservation, determined at record bearing and
distance from the witness corner established by Wilkes in 1917.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins.
in the ground, to solid rock, supported in a mound of stone, 4
ft. base, to top, with brass cap mkd.

T 2 S R 34 E
U I R
64 M
S 34
1988

from which

A fir, 15 ins. diam., bears S. 52½° E., 305 lks. dist.,
mkd. 64M UIR BT.

A ponderosa pine, 19 ins. diam., bears N. 29½° W.,
308 lks. dist., mkd. 64M UIR BT.

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.

From this point, the witness cor. to the 64 Mile Corner,
established by Wilkes in 1917 and perpetuated and recorded by
Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980,
bears West, 0.010 chs. dist., monumented with an iron post, 2
ins. diam., firmly set, protruding 30 ins. above ground, in a
mound of stone, 4 ft. base, to top, with brass cap mkd. T2S R34E
UIR 64 M WC, from which the remains of the bearing trees mkd. by
Wilkes:

A ponderosa pine, 9 ins. diam., bears N. 21½° E.,
134½ lks. dist., with partially healed blaze.
(Record, 133 lks.)

A rotted ponderosa pine stump, 33 ins. diam., bears
N. 49½° W., 252 lks. dist., with scribe mark T on
partially healed blaze.

UNION COUNTY
SURVEYOR
Date Received 3/8/13
Date Filed 3/8/13
By [Signature]
File No. 218-2013R

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHARGE

and a bearing tree mkd. by Barbour

A ponderosa pine, 8 ins. diam., bears S. $89\frac{3}{4}^{\circ}$ E.,
151 $\frac{1}{2}$ lks. dist., with illegible scribe marks on
partially healed blaze.

Bury the iron post in place.

West, on the 65th mile.

4.470 The closing cor. on the N. and S. center line of sec. 34, for
that portion of the section south of the Reservation boundary,
established and recorded by Barry B. Barbour, Registered Land
Surveyor No. 1051, in 1980, and is accepted as the corner,
monumented with an iron post, 2 ins. diam., firmly set,
protruding 8 ins. above ground, in a collar of stone, with brass
cap mkd.

T 2 S R 34 E

C

CC | S 34

C

OR PLS 1051

1980

from which the bearing trees mkd. by Barbour

A ponderosa pine, 14 ins. diam., bears S. 44° E.,
52 $\frac{1}{2}$ lks. dist., with scribe marks UIR C S34 CC BT
and a nail and washer at the base of partially healed
blaze.

A ponderosa pine, 13 ins. diam., bears S. 50° W.,
24 $\frac{1}{2}$ lks. dist., with scribe marks UIR C S34 CC BT
and a nail and washer at the base of partially healed
blaze.

West, beginning new measurement.

0.950 Point for the closing cor. on the N. and S. center line of sec.
34, for that portion of the section north of the Reservation
boundary, hereinafter described.

10.70 Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 218-2013R

Retracement-Resurvey of the South Boundary

Original Umatilla Indian Reservation

Chains

At exact cor. point
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for 63 Mile Cor., with brass cap marked

T25R34E
UIR
63M
1917

from which

A pine, 48 ins. diam., bears N.44°30'W., 53 lks. dist., marked in bark 63 M U R B T (old B.T.)

A pine, 48 ins. diam., bears S.83°50'E., 28 lks. dist., marked in bark 63 M U R B T (old B.T.)

I remove these marks and cut the marks in the wood.

Thence

N.89°42'E., resurveying 63rd Mile

Over mountainous land, through heavy timber and medium undergrowth.

Ascend 250 ft. to

24.00 Top of ascent, bears N. and SE.; enter rolling land.

32.30 The SE. angle cor. of Umatilla Indian Reservation.

Land, mountainous and bench.

Soil, light loam, shallow, on basalt bedrock; 2nd rate.

Timber, pine, fir and balsam.

Undergrowth, fir, balsam and willow.

From the 63 Mile Cor.

West, retracing the 64th Mile

40.26 Pass 5 lks. S. of the 63 $\frac{1}{2}$ Mile Cor., hereinafter described.

80.39 Fall 18 lks. S. of the 64 Mile Cor., which is a basalt stone, 18x14x6 ins., marked 64 M on W. face, set in a small mound of stone.

At a point 1 lk. W. of cor.

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, 1 $\frac{1}{2}$ ft. high, for witness cor. to the 64 Mile Cor., with brass cap marked

UNION COUNTY SURVEYOR	
Date Received	<u>3/11/13</u>
Date Filed	<u>3/11/13</u>
By	<u>J. G. S. L. DEPUTY</u>
File No.	<u>265-2013R</u>

Retracement-Resurvey of the South Boundary
Original Umatilla Indian Reservation

Chains

T2SR34E
UIR WG
64M
1917

from which

A pine, 24 ins. diam., bears N.49°30'W., 252 lks.
dist., marked U I R 64 M B T.

A pine, 6 ins. diam., bears N.21°45'E., 133 lks.dist.,
marked U I R 64 M B T.

thence

S.89°49'E., resurveying the 64th Mile

Over mountainous land, not very rough, through heavy timber
and medium undergrowth.

Descend 210 ft. to

16.25 Road, bears N. and S., in gulch, course S.; ascend 175
ft. to

28.80 Top of ascent, descends NW.

Descend on NE. and E. slope, 125 ft. to

34.87 The closing cor. of secs. 34 and 35, which is an old post,
much decayed, marked C C U R on N. face. In its place
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for closing cor. of secs. 34 and 35, with brass
cap marked

T2SR34E
C C
S34/S35
1917

from which

A fir, 16 ins. diam., bears S.19°30'W., 25 lks. dist.,
blazes grown over and unopened.

Other tree dead and fallen.

A lodgepole pine, 8 ins. diam., bears N.15°E., 39 lks.
dist., marked C C T 2 S R 34 E S 35 U I R B T. (new
B.T.)

A lodgepole pine, 6 ins. diam., bears N.44°W., 33 lks.
dist., marked C C T 2 S R 34 E S 34 U I R B T (new
B.T.)

40.13 The 63 $\frac{1}{2}$ Mile Cor., the position of which is determined

UNION COUNTY
SURVEYOR

Date Received 3/11/13

Date Filed 3/11/13

By C. J. & L. DEPUTY

File No. 265-2013R


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. MP-64

History of original corner establishment:

Corner was recovered by L. Wilkes, survey group No. 38, during October, 1917. Surveyor General's notes state: "Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground to bed-rock, in a mound of stone, 5 ft. base, 1 1/2 ft. high, for witness cor. to the 64 Mile cor., with brass cap marked:

T2SR34E
UIR WC
 64M
 1917



from which: A pine, 24 ins. diam., bears N49°30'W., 252 lks. dist. marked UIR64M BT.
 A pine, 6 ins. diam. bears N21°45'E., 133 lks. dist. marked UIR64M BT."

Description of corner evidence found:

Found 2" iron pipe and brass cap loosely set in mound of stone, 0.65 ft. west from firmly set marked stone. From which: A 9" pine bears N22°E, 88.8 ft. with grown over blaze, partially visible scribing.

Description of monument and accessories established to perpetuate the original location of this corner:

At the above point, reset the pipe with earth and large mound of rock.
 From which: An 8" pine bears S89 1/2°E, 100.0 ft. scribed UIR MP 64 WC BT. Painted blazes red and 6" red band around.
 Placed 54-3s, 54-4s and brass washers stamped PLS 1051.
 Placed 54-2 and 54-4 on steel fence post 5' east of the corner.

Pipe stamped:

T2S R34E
UIR WC
 M64
 1917

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
 Doug Moser

October 23, 1980

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Barry B. Barbour

OREGON
 OCT. 17, 1975
 BARRY B. BARBOUR
 1051

REFER TO SURVEY 10-81

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
NARRATIVE DRAWER 1/3	
File No.	_____

Office of...County...Surveyor..... County of..... Union
 State of...Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 30th day of...January....., 1981.

..... by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	☆ GPO-798-276 3/12/13
Date Filed	3/12/13
By	<i>SL DEATY</i>
File No.	282-2013R