

724

Retracement-Resurvey of the South Boundary

Original Umatilla Indian Reservation

Chains

dist., marked U I R 67 M B T (old B.T.)

A fir, 24 ins. diam., bears S.61°E., 21 lks. dist.,
marked U I R 67 M B T (old B.T.)

A fir, 20 ins. diam., bears N.23°W., 58 lks. dist.,
blazes healed over (old B.T.)

A pine, 22 ins. diam., bears N.46°30'W., 86 lks.
dist., marked U I R 67 M B T (old B.T.)

Thence

S.89°55'E., resurveying the 6th Mile

Over heavily rolling land, through scattering timber.

34.13 Intersect the closing cor. of secs. 31 and 32, which is
an old post in place, marks illegible. At exact cor.
point

UNION COUNTY SURVEYOR	
Date Received	<u>3/11/13</u>
Date Filed	<u>3/11/13</u>
By	<u>[Signature] DEPUTY</u>
File No.	<u>270-2013R</u>

Set a basalt stone, 18x12x10 ins., 12 ins. in the ground,
marked C C U R on N., 31 on W., 32 on E., in a ring of
stone; from which

A pine, 40 ins. diam., bears N.42°E., 120 lks. dist.,
marked U R C C B T. I mark additionally, T 2 S R
34 E S 32 (Lower blaze healed over and not opened).

A pine, 24 ins. diam., bears N.56°45'W., 77 lks. dist.,
marked U R C C B T. I mark additionally, T 2 S R
34 E S 31 (Lower blaze healed over and not opened).

36.20 Wood road, bears N. and S.

40.27 Intersect the 66th Mile Cor., which is an old post, much
decayed, marks illegible. At the exact cor. point
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for 66th Mile Cor., with brass cap marked

T2SR34E
UIR
66thM
1917

from which

A fir, 16 ins. diam., bears S.47°30'E., 42 lks.
dist., marked U R $\frac{1}{2}$ M B T (old B.T.)

A fir, 10 ins. diam., bears N.74°30'E., 16 lks.
dist., marked U R $\frac{1}{2}$ M B T (old B.T.)

Retracement-Resurvey of the South Boundary

Original Umatilla Indian Reservation

Chains

A tamarack, 5 ins. diam., bears N.47°E., 27 lks. dist., marked U I R 66 1/2 M B T (new B.T.)

Thence

S.89°52'E., continuing my measurements

Descend gradually.

54.89 A spring, flowing SE., bears South, 25 lks. dist.

Ascend gradually.

80.26 The 66 Mile Cor., heretofore described.

Land, mountainous, near top of high ridge, not very rough.

Soil, shallow; 2nd rate.

Timber, yellow pine, tamarack, fir and lodgepole pine.

Undergrowth, lodgepole pine on N. slope and balsam and willow.

From the 67 Mile Cor.

West, retracing the 68th Mile

40.37 Pass 15 lks. N. of the 67 1/2 Mile Cor., hereinafter described.

45.40 Fall 20 lks. N. of angle cor., which is an old post, 3x5 ins. sq., 30 ins. above ground, marked U R on E., 1/2 on S. face; no stone or mound of stone near the post. At exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for angle cor. of Umatilla Indian Reservation, with brass cap marked

T2S
R33E R34E
SW COR
UIR

1917

from which

A fir, 6 ins. diam., bears N.35°W., 13 lks. dist., marked \wedge U I R B T (new B.T.)

A fir, 8 ins. diam., bears N.46°E., 45 lks. dist., marked \wedge U I R B T (new B.T.)

A pine, 36 ins. diam., bears S.25°W., 54 lks. dist., marked U R \wedge B T. (old B.T. not mentioned in

UNION COUNTY SURVEYOR

Date Received 3/11/13

Date Filed 3/11/13

By *[Signature]* DEPUTY

File No. 270-2013

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


Index File No. M. P. 66 1/2

History of original corner establishment:

Corner was recovered by L. Wilkes, survey group No. 38, in October, 1917. Surveyor General's notes state: "Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for 66 1/2 Mile Cor., with brass cap marked: from which:

A fir, 16 ins. diam., bears S47°30'E, 42 lks. dist., marked UR 1/2 M BT (old BT).
 A fir, 10 ins. diam., bears N74°30'E, 16 lks. dist., marked UR 1/2 M BT (old BT).
 A tamarack, 5 ins. diam. bears N47°E, 27 lks. dist., marked UIR 66 1/2 M BT (new BT)."

T2S R34E
UIR
 66 1/2 M.
 1917



Description of corner evidence found:

Found 2" iron pipe with brass cap marked: Pipe projecting 12" above the ground. From which by magnetic declination of N20°E: A 24" dead fir bears S47 1/2°E, 28.6 ft. bark scribed UIR M66 1/2 BT. No trace of other BT.

T2S R34E
UIR
 66 1/2 M
 1917


Description of monument and accessories I established to perpetuate the original location of this corner:

Built mound of stone around to cap. From which a 15" fir bears N12° E, 28.3 ft. scribed UIR MP66 1/2 BT. A 12" fir bears S21°W, 38.3 ft. scribed UIR MP66 1/2 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s, and brass washers stamped PLS 1051 on the BTs. Placed 54-3 on the old BT. Placed 54-2 and 54-4 on a steel fence post 5' west of the mile post.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
 Doug Moser
 Ron Gilroy

November 6, 1980



Barry B. Barbour
 OREGON
 OCT. 17, 1975
 BARRY B. BARBOUR
 1051

UNION COUNTY SURVEYOR
Date Received _____
Date Filed _____
By _____
NARRATIVE DRAWER 1/3 File No. _____

REFER TO SURVEY 10-81

Office of.....County Surveyor..... County of..... Union.....
 Oregon
 State of..... Oregon....., I hereby certify that the within instrument was filed in this office for record on the 30th day of..... January....., 1981.

..... by
 (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
☆ GPO—798-276
Date Received <u>3/12/13</u>
Date Filed <u>3/12/13</u>
By <u>M & L DEPUTY</u>
File No. <u>280-2013R</u>