HOW COLLEGE

Retracement-Resurvey of the South Boundary
Original Umatilla Indian Reservation

Chains

field notes)

Thence

N.89°25'E., a true line, resurveying the 68th Hile. Over rolling land, through scattering timber.

5.03

Intersect the 672 Mile Cor., which is a basalt stone, 16x12x6 ins., marked but not legible, in a mound of stone.

Reset above stone, 12 ins. in the ground and mark it $67\frac{1}{2}$ M on W. and U R on H. face; from which

- A pine, 24 ins. diam., bears N.45°30°E., 175 lks. dist., marked U R $\frac{1}{2}$ M B T (old B.T.)
- A fir, 10 ins. diam., bears N.82°30°W., 330 lks. dist., marked U I R $67\frac{1}{8}$ H B T (new B.T.)

Thende

1.89°47'E., continuing my measurements

45.40 The 67 Mile Gor., heretofore described.

Land, rolling.

Soil, light loam, scant, on baselt bedrock; 2nd rate. Timber, scattering pine.

Undergrowth, nane.

Table of Partia Rast Bdy. . Z. 2 S., R. 34 E.

UNION COUNTY SURVEYOR

Date Received 3/11/13

Date Filed 3/11/3

By Sty & L DEPUTY

File No. 272-2013R

Net en demants

com the cor. of sees. 1, 18, 19 and 24, on the E. bdy. of the Tp., North retraing the line bet. sees. 13 and 10, at 40.23 chs. page 1 lbs. W. of the tree. cor., and at 60.40 who. fail 10 lks. V. of the cor. of secs.

forth vetracing the line bet. ecs. 7 and 12; at 40.29 ehs. fall 19 11. W. of the greet sor. First half mule lying out of lines and the line subject to rectification, I continue an measurements, setting temp. cors. and at 2 miles, 82 les. fall 19 les. W. of the cor. of Eps. 1 and 2 S., Rs. 74 and 35 E.

Townsena, at the cor. of secs. 13, 14, 19 and 24, on the B. bow. of the Ep., which is a volcante stone, 5x3x1 ft. above ground, not marked. At the exact cor. point as determined by the original bearing trees, cut a cross (x) for cor. of secs. 13, 16, 19 and 24, marked with 3

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. MP 67 1/2

History of original corner establishment:

Corner was recovered by L. Wilkes, survey group No. 38, in October, 1917. Surveyors General's notes state: "Intersect the 67 1/2 Mile cor., which is a basalt stone, 16x12x6 ins. marked but not legible. in a mound of stone. Reset above stone, 12 ins. in the ground and marked it 67 1/2 M on W face and UR on N face; from which: A pine, 24 ins. dia. bears Nº5°30'E, 175 lks. dist. marked UR1/2M BT (Old BT). A fir, 10 ins. diam. bears N82°30'W., 350 lks. dist. marked U1R67 1/2M BT."

DIAGRAM
T2S R3LE
UlR
67 1/2 MP

Description of corner evidence found:

Found 15x12x6 inch stone firmly set and marked UR on north side. From which: A 30" pine bears N46°E, 115.7 ft. with partially opened blazes and scribing. A 24" fir bears N82°W, 217.8 ft. visible scribing on partially opened blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the center of the above stone set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 22" in the ground and mound of stone around to cap. Buried marked stone alongside, from which by magnetic declination of N20°E:

T2S R34E <u>UlR</u> 67 1/2 MP OR PLS 1051 1980

A 12" pine bears S42°E, 18.2 ft. scribed UlRMP67 1/2 BT. Painted blazes red and 6" red bend around. Placed 54-3, 54-4 and brass washers stamped PLS 1051 on BTs. Placed 54-3 and 54-4 on old BTs. Placed 54-2 and 54-4 on steel fence post 5' east of the corner.

I hereby certify that the above corner monument was reestablished as herein described.

REGISTERED
PROFESSIONAL
AND SURVEYOR

OREGON oct. 17. 1975 BARRY E. BARBOUR 1 0 5 1 Witnesses: Daniel Rowland

Doug Moser Ron Gilroy

November 6, 1980

UNION COUNTY SURVEYOR

Date Received

Date Filed

NARRATIVE DRAWER /

REFER TO SURVEY 10-81

Office of County Sunveyor County of Union

State of ... Oregon ... I hereby certify that the within instrument was filed in this office for record on the 30th day of ... January 1821

(COUNTY, OFFICIAL)

(DEPUTY)

SURVEYOR

UNION COUNTY

Date Received 208.276 3/12/13

Date Filed 3/12/13

By 4 5 - SEAU File No. 278 -2013

Form R6-7100-57 (9/71)