

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS	
	<p>A ponderosa pine, 14 ins. diam., bears N. 29½° W., 374 lks. dist., with scribe marks T2S R34E S33 BT and with a nail and washer at the base of partially healed blaze.</p> <p>The corner is located on level, rocky ground.</p> <p>From this point, the 65 Mile Corner on the S. bdy. of the Umatilla Indian Reservation, bears N. 89° 35' 30" W., 34.840 chs. dist., hereinbefore described.</p>
<p>UNION COUNTY SURVEYOR</p> <hr/> <p>Date Received <u>3/8/13</u></p> <p>Date Filed <u>3/8/13</u></p> <p>By <u>[Signature] DEPUTY</u></p> <p>File No. <u>224-2013R</u></p>	<p>From the ¼ sec. cor. of secs. 33 and 34. N. 0° 10' 30" W., bet. secs. 33 and 34.</p>
	<p>Over level rocky prairie.</p>
5.10	<p>Dirt road, 20 lks. wide, bears N. 65° W. and S. 70° E.</p>
9.30	<p>Enter timber, edge bears E. and W.; desc. gentle N. slope.</p>
36.40	<p>Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.</p>
40.225	<p>The cor. of secs. 27, 28, 33, and 34, perpetuated by person(s) unknown, monumented with a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:</p> <p>A ponderosa pine, 35 ins. diam., bears N. 79° E., 137½ lks. dist., with scribe marks S27 on partially healed blaze, facing S. 10° W. (Record, N. 85° E., 142 lks.)</p> <p>A ponderosa pine, 28 ins. diam., bears S. 67½° E., 30 lks. dist., with axe marks on upper partially healed blaze and lower healed blaze. (Record, S. 76° E.)</p> <p>A rotted pine stump, 36 ins. diam., bears S. 60° W., 209 lks. dist., no marks visible. (Record, 200 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 2 S R 34 E S 28 S 27 S 33 S 34 1987</p>

MP 65

T2S34
V13

454

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 28 ins. diam., bears S. 70° W., 201½ lks. dist., mkd. T2S R34E S33 BT.

A ponderosa pine, 26 ins. diam., bears N. 20° W., 208 lks. dist., mkd. T2S R34E S28 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

The corner is located on level ground, 285 lks. S. of a dirt road, 15 lks. wide, bears N. 25° W. and S. 20° E., and 55 lks. W. of the same dirt road, bears N. and S.

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 55' 00" W., bet. secs. 27 and 34.

Over level ground, through timber and light undergrowth.

0.55 Gravelled road, 20 lks. wide, bears N. 60° W. and S. 60° E.

8.90 Same road, bears N. 70° E. and S. 60° W.

20.140 Point for the E 1/16 sec. cor. of secs. 27 and 34.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

E 1/16 S 27
S 34
1987

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature]

File No. 224-2013R

from which

A fir, 13 ins. diam., bears S. 56½° W., 60 lks. dist., mkd. E 1/16 S34 BT.

A fir, 15 ins. diam., bears N. 27¾° W., 22½ lks. dist., mkd. E 1/16 S27 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

35.55 Enter prairie, edge bears N. and S.

38.20 Dirt road, 15 lks. wide, bears N. 25° W. and S. 25° E.