

T2S34V15

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

40.280

The 1/4 sec. cor. of secs. 27 and 34, perpetuated by David H. Krumbein, Registered Land Surveyor No. 933, in 1971, as shown on a plat held at the Bureau of Indian Affairs, Mission, Oregon; monumented with an iron post, 2 ins. diam., firmly set, protruding 24 ins. above ground, in a mound of stone, 3 ft. base, to top (lying alongside is the original basalt stone, 12 x 10 x 10 ins., mkd. 1/4), with brass cap mkd. INDIAN ALLOTMENT 1919.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 2 S R 34 E

1/4 S 27

S 34

1987

T2S34  
V15

from which

A lodgepole pine, 9 ins. diam., bears S. 12 3/4° W., 65 lks. dist., mkd. 1/4 S34 BT.

A larch, 34 ins. diam., bears N. 68 3/4° W., 217 1/2 lks. dist., mkd. 1/4 S27 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the original stone and allotment pipe alongside the stainless steel post.

The corner is located on level ground, 95 lks. E. of timber, edge bears N. 20° W. and S. 60° E.

From the 1/4 sec. cor. of secs. 27 and 28, monumented with the original basalt stone, 12 x 8 x 7 ins., firmly set, protruding 8 ins. above ground, mkd. 1/4 on the W. face, in a mound of stone, 3 ft. base, 1 ft. high.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E

1/4

S 28 | S 27

1987

T2S34  
T13

UNION COUNTY  
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By *[Signature]* DEPUTY

File No. 225-2013R