

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 28 ins. diam., bears S. 70° W., 201 $\frac{1}{2}$ lks.
dist., mkd. T2S R34E S33 BT.A ponderosa pine, 26 ins. diam., bears N. 20° W.,
208 lks. dist., mkd. T2S R34E S28 BT.Deposit a white "DEEP-1" magnetic marker at the base and set a
steel fence post alongside the stainless steel post.The corner is located on level ground, 285 lks. S. of a dirt
road, 15 lks. wide, bears N. 25° W. and S. 20° E., and 55 lks. W.
of the same dirt road, bears N. and S.**UNION COUNTY
SURVEYOR**Date Received 3/8/13Date Filed 3/8/13By J. H. L. DerryFile No. 226-2013R

From the cor. of secs. 26, 27, 34, and 35.

S. $89^{\circ} 55' 00''$ W., bet. secs. 27 and 34.

Over level ground, through timber and light undergrowth.

0.55 Gravelled road, 20 lks. wide, bears N. 60° W. and S. 60° E.8.90 Same road, bears N. 70° E. and S. 60° W.

20.140 Point for the E 1/16 sec. cor. of secs. 27 and 34.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins.
in the ground, in a collar of stone, with brass cap mkd.E 1/16 S 27
 S 34
 1987T2S34
V16

from which

A fir, 13 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ W., 60 lks. dist.,
mkd. E 1/16 S34 BT.A fir, 15 ins. diam., bears N. $27\frac{3}{4}^{\circ}$ W., 22 $\frac{1}{2}$ lks. dist.,
mkd. E 1/16 S27 BT.Deposit a white "DEEP-1" magnetic marker at the base and set a
steel fence post alongside the stainless steel post.

35.55 Enter prairie, edge bears N. and S.

38.30 Dirt road, 15 lks. wide, bears N. 25° W. and S. 25° E.