

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

TRAINS	
6.70	Creek, dry, 2 lks. wide, drains generally N. 30° W.; thence over level ground.
20.255	<p>Point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 S 26 S 35 1987</p> <p>from which</p> <p>A lodgepole pine, 7 ins. diam., bears S. 58° W., 42½ lks. dist., mkd. W 1/16 S35 BT.</p> <p>A fir, 28 ins. diam., bears N. 22½° W., 60½ lks. dist., mkd. W 1/16 S26 BT.</p> <p>A United States Geological Survey brass tablet, 3 ins. diam., firmly set in a basalt ledge, mkd. 4291 FT 11AA 1950, bears S. 5° 24' E., 383 lks. dist.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.</p> <p>The corner is located on level ground, 275 lks. N. of a gravelled road, 30 lks. wide, bears N. 35° W. and S. 40° E.</p>
22.30	Gravelled road, 30 lks. wide, bears N. 35° W. and S. 35° E.
24.85	Creek, dry, 2 lks. wide, drains N. 15° W.
37.00	Creek, dry, 2 lks. wide, drains N. 5° W.
40.510	The cor. of secs. 26, 27, 34, and 35.
	N. 0° 15' 00" W., bet. secs. 26 and 27.
	Over level ground, through timber and light undergrowth.
20.195	<p>Point for the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>