

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 59' 30" W., bet. secs. 26 and 35.

Ascend steep SE. slope, through timber and light undergrowth.

10.65 Top of ascent; thence over level ground.

28.60 Dirt road, 20 lks. wide, bears N. 10° E. and S. 10° W.

33.75 Begin descent over W. slope.

40.205 The ¼ sec. cor. of secs. 26 and 35, monumented with the original basalt stone, 24 x 12 x 12 ins., firmly set, protruding 12 ins. above ground, mkd. ¼ on the N. face, from which the remains of the original bearing trees:

A ponderosa pine snag, 19 ins. diam., bears N. 72½° E., 60 lks. dist., with scribe marks ¼ S on partially healed blaze. (Record, N. 75° E., 34 lks.)

A ponderosa pine, 24 ins. diam., bears S. 62° E., 37 lks. dist., with scribe marks ¼ S on upper partially healed blaze and with healed lower blaze. (Record, S. 65° E., 34 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 2 S R 34 E

¼ S 26

S 35

1987

from which a new bearing tree

A fir, 15 ins. diam., bears N. 20° W., 2½ lks. dist., mkd. ¼ S26 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the original stone and steel fence post alongside the stainless steel post.

The corner is located on W. slope in timber.

S. 89° 51' 00" W., beginning new measurement.

UNION COUNTY  
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By J. L. Deary

File No. 229-2013R

T2S34  
V19