

by by by

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS									
39.60	Creek, 1 lk. wide, course N. 50° E. : see SE slope.								
40.100	The cor. of secs. 25, 26, 35, and 36, monumented with the original unmarked basalt stone, 12 x 10 x 10 ins., firmly set in a collar of stone.								
	At the corner point								
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.								
	<table border="0"> <tr><td>T 2 S</td><td>R 34 E</td></tr> <tr><td>S 26</td><td>S 25</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td colspan="2">1987</td></tr> </table>	T 2 S	R 34 E	S 26	S 25	S 35	S 36	1987	
T 2 S	R 34 E								
S 26	S 25								
S 35	S 36								
1987									
	from which								
	A fir, 10 ins. diam., bears N. 21¾° E., 41 lks. dist., mkd. T2S R34E S25 BT.								
	A fir, 29 ins. diam., bears S. 70¼° E., 33 lks. dist., mkd. T2S R34E S36 BT.								
	A fir, 10 ins. diam., bears S. 29¾° W., 18½ lks. dist., mkd. T2S R34E S35 BT.								
	A fir, 9 ins. diam., bears N. 71¼° W., 18½ lks. dist., mkd. T2S R34E S26 BT.								
	Deposit a white "DEEP-1" magnetic marker at the base and the original stone alongside the stainless steel post.								
	From the ¼ sec. cor. of secs. 34 and 35, monumented with a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:								
	A ponderosa pine snag, 30 ins. diam., bears N. 30° E., 113 lks. dist. with scribe marks ¼ S on partially healed blaze. (Record, N. 20° E., 104 lks.)								
	A ponderosa pine stump, 24 ins. diam., bears S. 74¼° W., 71½ lks. dist., no marks visible. (Record, S. 70° E., 73 lks.)								
	At the corner point								
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.								

T2S34 V21

T2S34 X17

UNION COUNTY SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature]

File No. 230-2013R