

T2S 34 W15

61

489

Subdivision of Section 34,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

C
N 1/16 | S 34
C
1987

T2S 34
W15

from which

A ponderosa pine, 8 ins. diam., bears S. $56\frac{3}{4}^{\circ}$ E.,
 $44\frac{1}{2}$ lks. dist., mkd. CN 1/16 S34 BT.

A fir, 12 ins. diam., bears S. $45\frac{3}{4}^{\circ}$ W., $75\frac{1}{2}$ lks. dist.,
mkd. CN 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

The corner is located on SE. slope.

26.00 Dirt road, 15 lks. wide, bears N. 60° E. and S. 55° W.

29.80 Ravine, drains S. 70° E.

38.40 Ravine, drains N. 55° E.

39.850 Point for the center $\frac{1}{4}$ sec. cor. of sec. 34, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 2 S R 34 E
C $\frac{1}{4}$ S 34
1987

T2S 34
X15

from which

A ponderosa pine, 23 ins. diam., bears S. $17\frac{1}{2}^{\circ}$ E.,
 $150\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S34 BT.

A fir, 16 ins. diam., bears S. $48\frac{1}{2}^{\circ}$ W., 72 lks. dist.,
mkd. C $\frac{1}{4}$ S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

40.20 Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.