


Index
 File No. W-16
 T 25 R. 34E
 Merid. WILLAMETTE

CORNER RECORD (SEARCH)

Tract or
 Survey No. _____
 Cor. N.E. 1/6 COR.
 No. SEC 34

R.D. LA GRANDE County UNION
 N.F. WALLOWA-WHITMAN State OREGON

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

1/6 COR. FOUND. 38 CHS. (25') SOUTH OF
Q OF S 214

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

27
 -|-|-| ← 2 & SPUR RD. 1090' N. TO 1/6 COR.
-	-	-

PHOTO IDENTIFICATION DATA

Photo No. UBM-0 6C-24
 Filed At. _____
 Object Ident. _____
 Ident. By _____

Signature

PLANE COORDINATE POSITION DATA

State _____ Zone _____
 X _____
 Y _____
 Estab. By _____

Agency

Signature

Title

Division

Headquarters

Date

7100-52

WHITMAN

LA GRANDE

1966

REV. 65 5

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 43-87B

W-16

Subdivision of Section 34,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C E 1/16 C
S 34
1987

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 232-2013R

from which

A larch, 32 ins. diam., bears S. 27½° E., 147 lks. dist. mkd. CE 1/16 S34 BT.

A fir, 9 ins. diam., bears N. 67° W., 39 lks. dist., mkd. CE 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

The corner is located on N. 80° E. slope.

40.280 The center ¼ sec. cor. of sec. 34.

40.90 Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.

61.90 Dirt road, 20 lks. wide, bears N. 35° W. and S. 35° E.

68.60 Dirt road, 20 lks. wide, bears N. 70° W. and S. 55° E.

70.90 Dirt road, 20 lks. wide, bears N. 50° E. and S. 60° W.

80.300 The ¼ sec. cor. of secs. 33 and 34.

From the center E 1/16 sec. cor. of sec. 34.

N. 0° 05' 00" W., on the N. and S. center line of the NE¼ of sec. 34.

Ascend SW. slope, through timber and light undergrowth.

20.015 Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E. and W. center line of the NE¼.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

NE 1/16 S 34
1987

Subdivision of Section 34,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 232-2013R

from which

A fir, 10 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ E., 44 lks. dist.,
mkd. NE 1/16 S34 BT.

A ponderosa pine, 10 ins. diam., bears N. $70\frac{3}{4}^{\circ}$ W.,
21 $\frac{1}{2}$ lks. dist., mkd. NE 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a
steel fence post alongside the stainless steel post.

The corner is located on S. slope.

20.80 Gravelled road, 30 lks. wide, bears E. and W.

21.80 Rock ledge, 10 ft. high, bears N. 70° E. and N. 60° W.

23.20 Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E.

40.025 The E 1/16 sec. cor. of secs. 27 and 34.

From the N 1/16 sec. cor. of secs. 34 and 35.

N. $89^{\circ} 51' 00''$ W., on the E. and W. center line of the NE $\frac{1}{4}$ of
sec. 34.

Over level ground, through timber and light undergrowth.

20.140 The NE 1/16 sec. cor. of sec. 34.

24.00 Creek, dry, 3 lks. wide, drains S. 25° E.; asc. broken E. slope.

40.280 The center N 1/16 sec. cor. of sec. 34.

From the center E 1/16 sec. cor. of sec. 34.

S. $0^{\circ} 05' 30''$ W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec.
34, on a mean bearing of the E. and W. bdrs. of the SE $\frac{1}{4}$ of sec.
34 for that portion of the section north of the S. bdy. of the
Umatilla Indian Reservation.

9.10 Barbed wire fence, 4 strands, bears generally E. and W.

9.860 Intersect the S. bdy. of the Umatilla Indian Reservation.

Point for the closing cor. on the N. and S. center line of the
SE $\frac{1}{4}$ of sec. 34, for that portion of the section north of the
Reservation boundary.