

1734

Retracement-Resurvey of the South Boundary
Original Umatilla Indian Reservation

Chains

dist., marked U I R 67 M B T (old B.T.)

A fir, 24 ins. diam., bears S.61°E., 21 lks. dist.,
marked U I R 67 M B T (old B.T.)

A fir, 20 ins. diam., bears N. 89°W., 58 lks. dist.,
blazes healed over (old B.T.)

A pine, 22 ins. diam., bears N.45°30'W., 86 lks.
dist., marked U I R 67 M B T (old B.T.)

Thence

S.89°55'E., resurveying the 67th Mile

Over heavily rolling land, through scattering timber.

34.13

Intersect the closing cor. of secs. 31 and 32, which is
an old post in place, marks illegible. At exact cor.
point

Set a basalt stone, 16x12x10 ins., 12 ins. in the ground,
marked C C U R on N., 31 on W., 32 on E., in a ring of
stone; from which

A pine, 40 ins. diam., bears N.42°E., 120 lks. dist.,
marked U R C C B T. I mark additionally, T 2 S R
34 E S 32 (Lower blaze healed over and not opened).

A pine, 24 ins. diam., bears N.56°45'W., 77 lks. dist.,
marked U R C C B T. I mark additionally, T 2 S R
34 E S 31 (Lower blaze healed over and not opened).

36.20

Wood road, bears N. and S.

40.27

Intersect the 66 1/2 Mile Cor., which is an old post, much
decayed, marks illegible. At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for 66 1/2 Mile Cor., with brass cap marked

T2SR34E
UIR
66 1/2 M
91

from which

A fir, 16 ins. diam., bears S.47°30'E., 42 lks.
dist., marked U R 1/2 M B T (old B.T.)

A fir, 10 ins. diam., bears N.74°30'E., 16 lks.
dist., marked U R 1/2 M B T (old B.T.)

UNION COUNTY
SURVEYOR

Date Received 3/11/13

Date Filed 3/11/13

By [Signature] DEPUTY


File No. 274-201312

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-Y-5-N

History of original corner establishment:

Corner was recovered by L. Wilkes, survey group No. 38, during October, 1917. Surveyor General's notes state: "Set a basalt stone, 16x12x10 ins., 12 ins. in the ground, marked CCUR on N. 31 on W., 32 on E., in a ring of stone: From which: A pine, 40 ins. diam., bears N42°E, 120 lks. dist. marked URCC BT. I mark additionally, T2S R34E S32 (lower blaze healed over and not opened). A pine 24 ins. diam., bears N56°45'W, 77 lks. dist., marked URCC BT. I mark additionally T2S R34E S31 (lower blaze healed over and not opened)."



Description of corner evidence found:

Found 19 X 11 X 10 inch stone firmly set in ring of rock marked: CCUR on north, 31 on west, and 32 on east faces. From which: A 36" pine bears N57°W, 51.7 ft. with visible scribing. A 44" down pine, visible scribing, stump hole bears N42°E, 80 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the center of the above stone, set 2 1/2" X 30" galvanized pipe and brass cap marked:
Set pipe 24" in the ground and mound of stone around to cap.
Buried marked stone alongside.
From which by magnetic declination of N20°E:
A 14" pine bears N78°E, 61.2 ft. scribed T2S R34E S32 CC BT.
Painted blazes red and 6" red band around. Placed 54-3, 54-4, and brass washer stamped PLS 1051 on the BT. Old BTs are signed. Placed 54-4 on a steel fence post 5' east of the corner.

T2S R34E
UIR
C C
S31/S32
OR PLS 1051
1980

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Doug Moser
Ron Gilroy

November 6, 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour
OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

REFER TO SURVEY 10-81

Office of... County Surveyor... County of... Union
State of... Oregon... I hereby certify that the within instrument was filed in this office
for record on the... 30th day of... January... 1981

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Date Received _____
Date Filed _____
By _____
NARRATIVE DRAWER
File No. 1/3

UNION COUNTY SURVEYOR
★ GPO—798-278
Date Received 3/12/13
Date Filed 5/12/13
By [Signature]
File No. 294-2013R