

486

Subdivision of Section 33,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS
39.720

Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 34 E
C 1/4 S 33
1987

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By J. L. DePuy

File No. 238-2013R

from which

A fir, 6 ins. diam., bears S. 86° E., 39 1/2 lks. dist., mkd. C 1/4 S33 BT.

A larch, 27 ins. diam., bears S. 35 1/2° W., 32 lks. dist., mkd. C 1/4 S33 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

The corner is located in ravine, drains N. 50° E.

Ascend N. slope, through moderate timber.

50.465

Intersect the S. bdy. of the Umatilla Indian Reservation.

Point for the closing cor. on the N. and S. center line of sec. 33, for that portion of the section north of the Reservation boundary.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

C
S | 33
C | C
C
1987

from which

A fir, 13 ins. diam., bears N. 73° E., 38 lks. dist., mkd. S33 CC BT.

A ponderosa pine, 40 ins. diam., bears N. 22 1/4° W., 128 lks. dist., mkd. S33 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.