

451

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

N. 0° 37' 30" E., beginning new measurement.

6.30 Creek, dry, 2 lks. wide, drains W.

40.275 The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

T 2 S R 34 E
S 22 | S 23
S 27 | S 26
1917

from which the remains of the original bearing trees

A root hole, bears N. 10½° E., 36½ lks. dist., with a down pine, 12 ins. diam., lying alongside, with scribe marks S2 34 S on upper and BT on lower partially healed blazes. (Record, N. 17½° E.)

A fir, 36 ins. diam., bears S. 34° E., 34 lks. dist., with scribe marks S4 E on partially healed blaze. (Record, S. 29° E., 32 lks.)

A pine snag, 15 ins. diam., bears S. 60½° W., 87 lks. dist., with illegible scribe marks on rotted blaze. (Record, S. 64° W.)

and new bearing trees

A fir, 7 ins. diam., bears N. 30° E., 40 lks. dist., mkd. T2S R34E S23 BT.

A fir, 11 ins. diam., bears S. 34½° W., 60 lks. dist., mkd. T2S R34E S27 BT.

A fir, 12 ins. diam., bears N. 21½° W., 53 lks. dist., mkd. T2S R34E S22 BT.

Set a steel fence post alongside the iron post.

From the ¼ sec. cor. of secs. 33 and 34, monumented with the original basalt stone, 14 x 10 x 4 ins., firmly set, protruding 6 ins. above ground, mkd. ¼ on N. face, in a mound of stone, 3 ft. base, 2 ft. high.

At the corner point

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By JL Deary

File No. 240-2013R

T2S34
X13

452

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E
S $33\frac{1}{2}$ S 34
1987

from which

A ponderosa pine, 11 ins. diam., bears N. $16\frac{3}{4}$ ° E.,
543 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

A ponderosa pine, 27 ins. diam., bears N. $82\frac{3}{4}$ ° W.,
615 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the original stone and steel fence post alongside the stainless steel post.

The corner is located on level rocky prairie.

S. $0^{\circ} 13' 00''$ E., bet. secs. 33 and 34.

Over level rocky ground.

10.150

Intersect the S. bdy. of the Umatilla Indian Reservation at the closing cor. of secs. 33 and 34, for the north side of the Reservation boundary, perpetuated and recorded by Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980, from original evidence no longer visible; monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E
S $33\frac{1}{2}$ S 34
OR PLS 1051
1980

from which the bearing trees mkd. by Barbour

A ponderosa pine, 11 ins. diam., bears N. $59\frac{1}{4}$ ° E.,
215 $\frac{1}{2}$ lks. dist., with scribe marks T2S R34E CC BT
and with a nail and washer at the base of partially
healed blaze.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 240-2013R