

Retracement-Resurvey of the South Boundary  
Original Umatilla Indian Reservation

Chains

from which

- A lodgepole pine, 8 ins. diam., bears S.69°E., 9 lks. dist., marked U R 65 M B T (old B.T., now fallen)
- A lodgepole pine, 8 ins. diam., bears S.52°W., 24 lks. dist., marked U R 65 M B T (old B.T.)
- A lodgepole pine, 8 ins. diam., bears S.85°W., 27 lks. dist., marked U R 65 M B T (old B.T., now dead)
- A lodgepole pine, 8 ins. diam., bears S.79°E., 27 lks. dist., marked U I R 65 M B T (new B.T.)
- A lodgepole pine, 9 ins. diam., bears N.51°W., 44 lks. dist., marked U I R 65 M B T (new B.T.)
- A lodgepole pine, 7 ins. diam., bears N.87°E., 54 lks. dist., marked U I R 65 M B T (new B.T.)

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>3/11/13</u>
Date Filed	<u>3/11/13</u>
By	<u>J. L. DEPUTY</u>
File No.	<u>273-2013 R</u>

Thence

S.89°27'E., on a true line, resurveying 65th Mile.

Over mountainous land, through dense small timber.

A fence follows close to line.

Descend 100 ft. to

15.32 Jennings Creek bed, 30 lks. wide, course SSE., water in holes.

Leave dense small timber; enter scattering large timber.

Ascend 340 ft. to

54.87 Intersect line bet. secs. 33 and 34, at the closing cor., which is a basalt stone, 14x9x4 ins., marked U R on N. and C C on E. faces, in mound of stone, 6 ins. high. At a point 1 lk. N. of old closing cor. Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to the closing cor. of secs. 33 and 34, with brass cap marked

C C  
T2S R34E  
UIR  
S33 | S34  
WC  
1917

and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

452

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

UNION COUNTY  
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By JPL DEPUTY

File No. 241-2013R

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E  
¼  
S 33 | S 34  
1987

from which

A ponderosa pine, 11 ins. diam., bears N. 16¾° E.,  
543 lks. dist., mkd. ¼ S34 BT.

A ponderosa pine, 27 ins. diam., bears N. 82¾° W.,  
615 lks. dist., mkd. ¼ S33 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the original stone and steel fence post alongside the stainless steel post.

The corner is located on level rocky prairie.

S. 0° 13' 00" E., bet. secs. 33 and 34.

Over level rocky ground.

10.150

Intersect the S. bdy. of the Umatilla Indian Reservation at the closing cor. of secs. 33 and 34, for the north side of the Reservation boundary, perpetuated and recorded by Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980, from original evidence no longer visible; monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E  
UIR  
C | C  
S 33 | S 34  
OR PLS 1051  
1980

T2S34  
X13I

from which the bearing trees mkd. by Barbour

A ponderosa pine, 11 ins. diam., bears N. 59½° E.,  
215½ lks. dist., with scribe marks T2S R34E CC BT  
and with a nail and washer at the base of partially  
healed blaze.

453

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

A ponderosa pine, 14 ins. diam., bears N. 29½° W.,  
374 lks. dist., with scribe marks T2S R34E S33 BT  
and with a nail and washer at the base of partially  
healed blaze.

The corner is located on level, rocky ground.

From this point, the 65 Mile Corner on the S. bdy. of the  
Umatilla Indian Reservation, bears N. 89° 35' 30" W., 34.840 chs.  
dist., hereinbefore described.

From the ¼ sec. cor. of secs. 33 and 34.

N. 0° 10' 30" W., bet. secs. 33 and 34.

Over level rocky prairie.

5.10 Dirt road, 20 lks. wide, bears N. 65° W. and S. 70° E.

9.30 Enter timber, edge bears E. and W.; desc. gentle N. slope.

36.40 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.

40.225 The cor. of secs. 27, 28, 33, and 34, perpetuated by person(s)  
unknown, monumented with a mound of stone, 3 ft. base, 1 ft.  
high, from which the remains of the original bearing trees:

A ponderosa pine, 35 ins. diam., bears N. 79° E.,  
137½ lks. dist., with scribe marks S27 on partially  
healed blaze, facing S. 10° W. (Record, N. 85° E.,  
142 lks.)

A ponderosa pine, 28 ins. diam., bears S. 67½° E.,  
30 lks. dist., with axe marks on upper partially  
healed blaze and lower healed blaze. (Record, S. 76° E.)

A rotted pine stump, 36 ins. diam., bears S. 60° W.,  
209 lks. dist., no marks visible. (Record, 200 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins.  
in the ground, to solid rock, supported in a mound of stone, 3  
ft. base, to top, with brass cap mkd.

T 2 S R 34 E  
S 28 | S 27  
S 33 | S 34  
1987

UNION COUNTY  
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY


File No. 241-2013R

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

Index File No. X-Y-13-N

**History of original corner establishment:**

Corner was recovered by L. Wilkes, survey group No. 38, in October, 1917. Surveyor General's notes state: "At a point 1 lk. N. of old closing corner, Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground, for witness cor. to the closing cor. of secs. 33 and 34, with brass cap marked: and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor."



C C  
T2S R34E  
UIR  
S33 S34

W C  
1917

**Description of corner evidence found:**

Found no trace of 1917 brass cap witness corner. In mound of stone found loose 16" X 9" X 3" stone marked UR CC on one side. At a point about 10 chains north, found 14" X 10" X 4" stone marked with 4 on west side, in mound of stone. Established line from old CC mound and 1/4 corner to the north. Established line from MP 64 1/2 to south new closing corner of sections 33 and 34.

This point is 73.05 ft. from the new south closing corner. (Record 110 lks. dist.)

**Description of monument and accessories established to perpetuate the original location of this corner:**

At point of intersection, set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 12" in the ground to bedrock and mound of stone around to cap.



From which:

A 12" pine bears N61°E, 141.9 ft., scribed T2S R34E S34 CC BT. A 14" pine bears N29°W, 246.8 ft. scribed T2S R34E S33 CC BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s, and brass washers stamped PLS 1051 on the BTs. Placed 54-2 and 54-4 on a steel fence post 5' west of the corner.

OR PLS 1051  
1980

Placed 54-4 on a steel fence post 5' south of the 1/4 corner to the north.

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland  
Doug Moser  
Ron Gilroy

November 5, 1980

**REGISTERED PROFESSIONAL LAND SURVEYOR**

*Barry B. Barbour*  
OREGON  
OCT. 17, 1975  
BARRY B. BARBOUR  
1051

REFER TO SURVEY 10-81

Office of.....County.....Surveyor..... County of.....Union.....  
State of.....Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the..30th day of.....January....., 19..81

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY SURVEYOR**  
Date Received \_\_\_\_\_  
Date Filed \_\_\_\_\_  
By \_\_\_\_\_  
File No. NARRATIVE DRAWER 1/3

**UNION COUNTY SURVEYOR**  
☆ GPO—798-276  
Date Received 3/12/13  
Date Filed 3/12/13  
By [Signature] Deputy  
File No. 291-2013R