

T2534X16

Subdivision of Section 34,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C E 1/16 C
S 34
1987

from which

A larch, 32 ins. diam., bears S. 27½° E., 147 lks. dist., mkd. CE 1/16 S34 BT.

A fir, 9 ins. diam., bears N. 67° W., 39 lks. dist., mkd. CE 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

The corner is located on N. 80° E. slope.

- 40.280 The center ¼ sec. cor. of sec. 34.
- 40.90 Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.
- 61.90 Dirt road, 20 lks. wide, bears N. 35° W. and S. 35° E.
- 68.60 Dirt road, 20 lks. wide, bears N. 70° W. and S. 55° E.
- 70.90 Dirt road, 20 lks. wide, bears N. 50° E. and S. 60° W.
- 80.300 The ¼ sec. cor. of secs. 33 and 34.

From the center E 1/16 sec. cor. of sec. 34.

N. 0° 05' 00" W., on the N. and S. center line of the NE¼ of sec. 34.

Ascend SW. slope, through timber and light undergrowth.

20.015 Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E. and W. center line of the NE¼.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

NE 1/16 S 34
1987

T2534
X16

T2534
W16

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 244-2013R