

T2S34X16I

Subdivision of Section 34,  
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

UNION COUNTY  
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 245-2013R

from which

A fir, 10 ins. diam., bears S. 41½° E., 44 lks. dist.,  
mkd. NE 1/16 S34 BT.

A ponderosa pine, 10 ins. diam., bears N. 70¼° W.,  
21½ lks. dist., mkd. NE 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a  
steel fence post alongside the stainless steel post.

The corner is located on S. slope.

20.80 Gravelled road, 30 lks. wide, bears E. and W.

21.80 Rock ledge, 10 ft. high, bears N. 70° E. and N. 60° W.

23.20 Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E.

40.025 The E 1/16 sec. cor. of secs. 27 and 34.

From the N 1/16 sec. cor. of secs. 34 and 35.

N. 89° 51' 00" W., on the E. and W. center line of the NE¼ of  
sec. 34.

Over level ground, through timber and light undergrowth.

20.140 The NE 1/16 sec. cor. of sec. 34.

24.00 Creek, dry, 3 lks. wide, drains S. 25° E.; asc. broken E. slope.

40.280 The center N 1/16 sec. cor. of sec. 34.

From the center E 1/16 sec. cor. of sec. 34.

S. 0° 05' 30" W., on the N. and S. center line of the SE¼ of sec.  
34, on a mean bearing of the E. and W. bdrs. of the SE¼ of sec.  
34 for that portion of the section north of the S. bdy. of the  
Umatilla Indian Reservation.

9.10 Barbed wire fence, 4 strands, bears generally E. and W.

9.860 Intersect the S. bdy. of the Umatilla Indian Reservation.

Point for the closing cor. on the N. and S. center line of the  
SE¼ of sec. 34, for that portion of the section north of the  
Reservation boundary.

T2S34  
X16I

433

Subdivision of Section 34,  
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

E  
S | 34  
C | C  
E  
1987

from which

A lodgepole pine, 6 ins. diam., bears N. 39° E.,  
80 lks. dist., mkd. S34 CC BT.

A larch, 9 ins. diam., bears N. 65¾° W., 55½ lks. dist.,  
mkd. S34 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

From this point, the 64 Mile Corner on the S. bdy. of the Umatilla Indian Reservation, bears N. 89° 40' 30" W., 14.685 chs. dist., hereinbefore described.

UNION COUNTY  
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 245-2013R

Subdivision of Section 35,  
T. 2 S., R. 34 E., Willamette Meridian, Oregon

From the ¼ sec. cor. of secs. 26 and 35.

S. 0° 13' 30" W., on the N. and S. center line of sec. 35, on a mean bearing of the E. and W. bdrs. of that portion of sec. 35 north of the S. bdy. of the Umatilla Indian Reservation.

Over W. slope, through timber.

12.10 Dirt road, bears N. 80° E. and S. 70° W.

14.70 Descend SW. slope.

40.195 Point for the center ¼ sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C¼ S 35  
1987