

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS									
39.60	Creek, 1 lk. wide, course N. 50° E.; asc. SE. slope.								
40.100	The cor. of secs. 25, 26, 35, and 36, monumented with the original unmarked basalt stone, 12 x 10 x 10 ins., firmly set in a collar of stone.								
	At the corner point								
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.								
	<table border="0"> <tr><td>T 2 S</td><td>R 34 E</td></tr> <tr><td>S 26</td><td>S 25</td></tr> <tr><td>S 35</td><td>S 36</td></tr> <tr><td colspan="2" style="text-align: center;">1987</td></tr> </table>	T 2 S	R 34 E	S 26	S 25	S 35	S 36	1987	
T 2 S	R 34 E								
S 26	S 25								
S 35	S 36								
1987									
	from which								
	A fir, 10 ins. diam., bears N. 21½° E., 41 lks. dist., mkd. T2S R34E S25 BT.								
	A fir, 29 ins. diam., bears S. 70½° E., 33 lks. dist., mkd. T2S R34E S36 BT.								
	A fir, 10 ins. diam., bears S. 29¾° W., 18½ lks. dist., mkd. T2S R34E S35 BT.								
	A fir, 9 ins. diam., bears N. 71½° W., 18½ lks. dist., mkd. T2S R34E S26 BT.								
	Deposit a white "DEEP-1" magnetic marker at the base and the original stone alongside the stainless steel post.								
	From the ¼ sec. cor. of secs. 34 and 35, monumented with a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:								
	A ponderosa pine snag, 30 ins. diam., bears N. 30° E., 113 lks. dist., with scribe marks ½ S on partially healed blaze. (Record, N. 20° E., 104 lks.)								
	A ponderosa pine stump, 24 ins. diam., bears S. 74½° W., 71½ lks. dist., no marks visible. (Record, S. 70° E., 73 lks.)								
	At the corner point								
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.								

UNION COUNTY SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 246-2013R

445

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

T 2 S R 34 E
¼
S 34 | S 35
1987

from which new bearing trees

A ponderosa pine, 15 ins. diam., bears S. 14½° E.,
33 lks. dist., mkd. ¼ S35 BT.

A ponderosa pine, 11 ins. diam., bears S. 50½° W.,
67 lks. dist., mkd. ¼ S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and a steel
fence post alongside the stainless steel post.

S. 0° 17' 00" W., bet. secs. 34 and 35.

Descend SE. slope, through timber and light undergrowth.

9.830 Intersect the S. bdy. of the Umatilla Indian Reservation.

True point for the closing cor. of secs. 34 and 35 for the north
side of the Reservation boundary.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 2 S R 34 E
C | C
S 34 | S 35
S 34
1987

T2S34
X17I

from which

A fir, 9 ins. diam., bears N. 71½° E., 41½ lks. dist.,
mkd. T2S R34E S35 CC BT.

A fir, 14 ins. diam., bears N. 30½° W., 37½ lks. dist.,
mkd. T2S R34E S34 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a
steel fence post alongside the stainless steel post.

From this point, the 64 Mile Corner on the S. bdy. of the
Umatilla Indian Reservation, bears N. 89° 40' 30" W., 34.790 chs.
dist., hereinbefore described.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By AL L DEPUTY

File No. 246-2012R