

Subdivision of Section 35,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS	
43.10	Dirt road, 15 lks. wide, bears N. 20° E. and S. 5° E.
45.80	Ravine, drains S. 25° W.
49.70	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
60.305	Point for the center W 1/16 sec. cor. of sec. 35. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground in fractured rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd. C W 1/16 C S 35 1987 from which A ponderosa pine, 19 ins. diam., bears N. 11½° E., 414 lks. dist., mkd. CW 1/16 S35 BT. A ponderosa pine, 9 ins. diam., bears S. 52½° W., 118 lks. dist., mkd. CW 1/16 S35 BT. Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post. Descend SW. slope, over prairie.
67.00	Dirt road, 15 lks. wide, bears N. 35° W. and S. 45° E.
75.80	Ravine, drains S. 20° W.
80.455	The ¼ sec. cor. of secs. 34 and 35. From the center W 1/16 sec. cor. of sec. 35. S. 0° 15' 00" W., on the N. and S. center line of the SW¼ of sec. 35 on a mean bearing of the E. and W. bdrs. of the SW¼ of sec. 35, for that portion of the section north of the S. bdy. of the Umatilla Indian Reservation. Descend SW. slope, over prairie.
4.30	Dirt road, 15 lks. wide, bears N. 65° W. and S. 65° E.
4.50	Enter timber, edge bears N. 80° E. and N. 65° W.
9.90	Barbed wire fence, 3 strands, bears E. and W.

T2S 34 X 18

UNION COUNTY SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 250-2013R