493

Subdivision of Section 34,

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.

C½ S 35 1987

T. 2 S., R. 34 E., Willamette Meridian, Oregon CHAINS Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. S | 34 clc UNION COUNTY 1987 SURVEYOR from which Date Received A lodgepole pine, 6 ins. diam., bears N 39° 80 1ks. dist., mkd. S34 CC BT. W., 55½ 1ks. dist.. A larch, 9 ins. diam., bears N. 652 mkd. S34 CC BT. Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post. From this point, the 64 Mile Corner on the S. bdy. of the Umatilla Indian Reservation, bears N 89° 40' 30" W., 14.685 chs. dist., hereinbefore described. Subdivision of Section 35 T. 2 S. R. 34 E., Willamette Meridian, Oregon From the z sec. cor. of secs. 26 and 35. S. 0° 13' 30" W., on the N. and S. center line of sec. 35, on a mean bearing of the E. and W. bdrs. of that portion of sec. 35 north of the S. bdy. of the Umatilla Indian Reservation. Over W. slope, through timber. Dert road, bears N. 80° E. and S. 70° W. 12.10 14.70 Descend SW. slope. Point for the center 4 sec. cor. of sec. 35, at intersection with 40.195 the E. and W. center line.

in the ground, with brass cap mkd.

Date Filed

File No.

## Subdivision of Section 35, T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

from which

- A larch, 12 ins. diam., bears N.  $49\frac{1}{2}^{\circ}$  E.,  $70\frac{1}{2}$  1ks. dist., mkd.  $C\frac{1}{4}$  S35 BT.
- A fir, 10 ins. diam., bears S.  $21\frac{1}{2}^{\circ}$  E., 20 lks. dist., mkd.  $C\frac{1}{8}$  S35 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

50.290

Intersect the S. bdy. of the Umatilla Indian Reservation.

Point for the closing cor. on the N. and S. center line of sec. 35, for that portion of the section north of the Reservation boundary.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam, 8 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

C C C S 35 C 1987

UNION COUNTY SURVEYOR

Date Received 🗅

Date Filed 3/8/3

y Aff DEDUTY

File No. 248 2013R

from which

- A ponderosa pine, 24 kms. diam., bears N. 31% E., 157 lks. dist., mkd. 335 CC BT.
- A fir, 20 ins. diam., bears N.  $16^{\circ}$  W.,  $104\frac{1}{2}$  lks. dist., mkd. S35 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

From this point, the 63 Mile Corner on the S. bdy. of the Umatilla Indian Reservation, bears S. 89 47' 00" E., 5.310 chs. dist., hereinbefore described.

From the 2 sec. cor. of secs. 35 and 36.

S.  $89^{\circ}$  52' 00" W., on the E. and W. center line of sec. 35.

- 2.20 Descend over NW. Slope, through heavy timber.
- 40.155 The center  $\frac{1}{4}$  sec. cor. of sec. 35.