

494

Subdivision of Section 35,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

from which

A larch, 12 ins. diam., bears N. $49\frac{1}{2}^\circ$ E., $70\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{2}$ S35 BT.

A fir, 10 ins. diam., bears S. $21\frac{1}{2}^\circ$ E., 20 lks. dist., mkd. C $\frac{1}{2}$ S35 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

50.290

Intersect the S. bdy. of the Umatilla Indian Reservation.

Point for the closing cor. on the N. and S. center line of sec. 35, for that portion of the section north of the Reservation boundary.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

C
C|C
S|35
C
1987

T2S 34
X19E

from which

A ponderosa pine, 24 ins. diam., bears N. $31\frac{3}{4}^\circ$ E., 157 lks. dist., mkd. S35 CC BT.

A fir, 20 ins. diam., bears N. 26° W., $104\frac{1}{2}$ lks. dist., mkd. S35 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

From this point, the 63 Mile Corner on the S. bdy. of the Umatilla Indian Reservation, bears S. $89^\circ 47' 00''$ E., 5.310 chs. dist., hereinbefore described.

From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

S. $89^\circ 52' 00''$ W. on the E. and W. center line of sec. 35.

2.20

Descend over NW. slope, through heavy timber.

40.155

The center $\frac{1}{4}$ sec. cor. of sec. 35.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By [Signature] DEPUTY

File No. 249-2013R