

Dependent Resurvey of a Portion of the South Boundary of
the Umatilla Indian Reservation,
T. 2 S., R. 34 E., Willamette Meridian, Oregon

CHAINS

Bury the iron post in place.

The corner is located on NE. slope, in timber and light undergrowth.

N. 89° 34' 30" W., beginning new measurement.

2.95 Dist road, 15 lks. wide, bears N. 40° W. and S. 40° E.

4.020 The closing cor. of secs. 33 and 34, for the south side of the Reservation boundary, established and recorded by Barry B. Barbour, Registered Land Surveyor No. 1051, in 1980, and is accepted as the corner, monumented with an iron post, 2 ins. diam., firmly set, protruding 20 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 34 E
U I R
S 33 | S 34
C | C
OR PLS 1051
1980

from which a bearing tree mkd. by Barbour

A ponderosa pine, 16 ins. diam., bears S. 61° E.,
341 lks. dist., with scribe marks T2S R34E S34 CC BT
and a nail and washer at base of partially healed blaze.

From this point, the original closing cor. of secs. 33 and 34 established by Wilkes in 1917, bears S. 2° 29' 00" E., 0.075 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, protruding 24 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T2S R34E UIR S33 S34 CC 1917, from which the remains of a bearing tree mkd. by Wilkes:

A root hole, bears S. 56½° W., 234 lks. dist., with ponderosa pine, 8 ins. diam., lying alongside, with scribe marks CC T2S R34E S3 BT on partially healed blaze.

Mark the brass cap AM and bury the iron post in place.

N. 89° 50' 30" W., beginning new measurement.

UNION COUNTY
SURVEYOR

Date Received 3/8/13

Date Filed 3/8/13

By JLL DEPUTY

File No. 258-2013R


Y12I

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-Y-13-S

History of original corner establishment:

Corner was originally established by L. Wilkes, survey group No. 38, during October, 1917. Surveyor General's notes state: "Set an iron post 3 ft. long, 2 ins. diam., 12 ins. in the ground and 12 ins. in a mound of stone, for closing corner of secs. 33 and 34, with brass cap marked:



From which: A pine, 6 ins. diam., bears T2S R34E S62°45'E, 167 lks. dist., marked CC T2S UIR R34E S34 BT. A pine, 8 ins. diam., bears S33 S34 S56°30'W, 234 lks. dist. marked CC T2S R34E C C S33 BT. The closing corner for that portion of secs. 33 and 34 within the original 1917 Unatilla Indian Reservation, bears N89°27'W, 110 lks. dist."


Description of corner evidence found:

Found 1917 brass cap as described above, loosely set in small mound of stone. Firmed up pipe with dirt and built mound of stone to cap. No trace of BTs.

From survey to MP 65, corner moves N0°04'W, 4.83 ft. to be on line.

Description of monument and accessories established to perpetuate the original location of this corner:

At the above described point set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 10" in the ground to bedrock and mound of stone around to cap. From which by magnetic declination of N20°E: A 15" pine bears S58°E, 228.0 ft. scribed T2S R34E S34 CC BT. No tree in Southwest Quadrant. Painted blazes red and 6" red band around. Placed 54-3 and 54-4 and brass washer stamped PLS 1051 on the BT. Placed 54-2 and 54-4 on a steel fence post 7' south and 54-2 on a steel fence post 5' west of the corner.



I hereby certify that the above corner monument was established as herein described.

Witnesses: Daniel Rowland
Doug Moser
Ron Gilroy

November 5, 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour
OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

REFER TO Survey 10-81

Office of.....County Surveyor..... County of..... Union.....
State of..... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 30th day of..... January....., 1981

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed _____

By _____

NARRATIVE DRAWER 1/3
File No. _____

UNION COUNTY SURVEYOR

* GPO—798-278

Date Received 3/12/13

Date Filed 3/12/13

By M & L Deary

File No. 290-2013R