


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. N-23

History of original corner establishment:

In 1882 under G.L.O. contract No. 451 Rufus S. Moore set post for 1/4 Sec. 13 and 24 from which: A Pine 9" bears N13°W 26 lks. A Pine 14" bears S64°W 29 lks.



Description of corner evidence found:

Could find no evidence of original post or BT's.

Description of monument and accessories I established to perpetuate the original location of this corner:

At single proportioned measurement between NW and NE of S24 T2S R35E set a 2 1/2" x 30" galvanized pipe with brass cap attached 24" in the ground stamped:

T2S R35E
S13
1/4 $\frac{13}{24}$
S24
1981
ORPLS 1099

From which:

A 6" Tamarack bears S87°W 23.0 ft. scribed 1/4 S24 BT.
A 6" Lodgepole Pine bears N19° W 16.9 ft. scribed 1/4 S13 BT.

Attached 54-3 and 54-4 signs to both BT's. Painted blazes and 6" red ring around trees. Attached brass washers LS 1099 to foot blazes. Set metal fencepost 5' West of corner with 54-4 signs.

Corner falls on N.W. slope 200 feet above bottom of gulch.

Compass Declination: 18 1/2° East.

I hereby certify the above described corner monument and/or accessories was established as described on November 9, 1981.

Witnesses: Loren Huntsman
Millard Wyatt



Office of Surveyor County of Union
Oregon
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 4 day of OCTOBER, 1982
Howard L. Perry by Gary L. Langlitz
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____
GPO 799-509
Date Filed _____
By _____
File No. 208-84R