## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:

In 1882 Rufus S. Moore under GLO Contract #451 set a basalt stone 18"x12"x10" 12 inches in the ground for Sec. Cor. to Sec. 23, 24, 25, 26. Stone was marked with 2 notches on S. and 1 notch on E. edges. From which:

A Tamarack 18" in dia. bears N  $16^{\circ}E$  23 lks. A Tamarack 12" in dia. bears N19°W 45 lks.

A Pine 9" in dia. bears S64°W 64 lks. A Pine 20" in dia. bears S21°E 24 lks.

Index File No. R-21

DIAGRA	М
T2S	R35E
23	24
26	25
'	

## Description of corner evidence found:

Stone 18"x12"x10" 6 inches in the ground with faint two notches on South & 1 notch on East edges. From Which:

An 8" Tamarack snag bears N16°E 15.2' with visible scribing "2S R35E S4"

An 8" Tamarack stump with log laying nearby bears N20°W 29.7' (log has healed blaze, no visible scribing). Stumps were also found at recorded direction and distance SE and SW with no scribing visible.

## Description of monument and accessories I established to perpetuate the original location of this corner:

At the location of the found stone, we set a 2"x30" Galvanized Iron Pipe 15" in the ground in a mound of stone, with brass cap attached marked:

Bury found stone alongside monument and mark the following new BT's:

From which:

An 11" white Fir bears N41°E 23.2 ft. scribed T2S R35E S24 BT

A 7" Tamarack bears N60°W 17.0 ft. scribed T2S R35E S23 BT. A 12" White Fir bears S56°W 13.5 ft. scribed T2S R35E S26 BT An 8" White Fir bears S37°E 13.5 ft. scribed T2S R35E S25 BT Attached 54-3, 54-4 signs to all BT's. Painted red blazes and ring around BT's. Also attached brass washer 1099 to foot blaze of new BT's.

Set metal fence post 5' north of corner with a 54-4 sign. Compass Declination: 18 1/2° East.

I hereby certify the above described monument and/or accessories were established on September 25, 1981.

Witnesses: Loren Huntsman Jeff Anderson Millard Wyatt

REGISTERED **PROFESSIONAL** AND SURVEYOR

T2S

\$23

\$26

R35E

**S24** 

S25

1981

OR PLS 1099

OREGON .. LANGLITZ 1099

File No. 218-84 R

Office of Surveyor County of Union	
State of Oregon I hereby certify that the within instrument was filed in the	is off <del>ice</del>
for record on the 4 day of OCTOBER 1982   1982   Howard L. Perry by Journal Langle	UNION COUNTY SURVEYOR
(COUNTY OFFICIAL)	
orm R6-7100-57 (9/71)	Ontra Roceived ★ GPO-798.275
	f Filed