


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.5 - 19

History of original corner establishment:

Corner was established as part of this survey.



Description of corner evidence found:

None.

Description of monument and accessories established to perpetuate the original location of this corner:

At position established by survey:

Set a 2½" X 30" aluminum pipe with a 2½" aluminum cap, buried 21" in the ground and surrounded with a mound of earth and stone.

Set a 6' steel fence post 4' North of monument and attached signs 54-2 and 54-9.

Set a 6' steel fence post 4' West of monument with sign 54-2 attached.

New bearing trees established:

A 12" ponderosa pine bears N 89° E - 128.2 ft., scribed "C-N-S 1/64 S26BT".

A 20" ponderosa pine bears S 78¼° W - 149.4 ft., scribed "C-N-S 1/64 S26BT".

New bearing trees have a brass washer stamped "PLS 1106" nailed to face of blaze. Attached sign 54-3 & 54-9, painted face of blaze & a 6" red band around each tree.

Bearing trees were tied using a Sokkia Automatic Total Station.

This corner falls on a Northwesterly slope in the South end of a rock pit.

I hereby certify that the above corner monument was properly monumented to U.S.F.S. standards by me on November 16, 1994.

Compass declination 18° East.

Witnessed by: Greg E. Flowers, LSIT  
Todd Rosenbalm

REGISTERED PROFESSIONAL LAND SURVEYOR
---

*With R. Wells*

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106
---

*renews 6/30/98*

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL)

UNION COUNTY SURVEYOR
(DEPUTY)
Date Received <u>7-10-96</u>
Date Filed <u>7-10-96</u>
By <u>R. ROBINSON, DEPUTY</u>
File No. <u>076-1996R</u>

\* GPO-788-276