
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-13

History of original corner establishment: Corner established in 1881 by Jacob C. Cooper, unerr General Land Office Contract No. 397.

Surveyor General records (notes) states: Set basalt stone 18x14x5, 8 ins. in the ground and made stone mound 2 ft. hith for cor. to sec. 3, 4, 33 & 34.

note: No restoration appears in the county records.



Description of corner evidence found:

Found a basalt stone 18x14x5 ins. in a mound of stone. The corner stone has obviously been disturbed, however remains of the original mound of stone are preasent & the section corner location is accepted as the center of the original stone mound.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 30"x2½" iron pipe with 3" brass capmarked as shown, 6" in the ground to solid rick &shiseled an "X" in the rock under the pipe for the corner to sections 33, 34, 4 & 3 & raised a mound of stone 6 ft. diam. & 3 ft. high around the pipe.

From which, new Bearing Trees
A Pine 20 ins. diam. bears N47°E 81.8 ft. dist. marked,
T1S R36E S34 BT

A Pine 14 ins. diam. bears S450E 81.6 ft. dist. marked, T2S R36E S3 BT

A Pine 7 ins. diam. bears S70°W 40.5 ft. dist. marked, T2s R36 E S4 BT

T I S R 36E

S 33 S 34
S 4 S 3

T 2 S
19 72 PLS 608

REGISTERED PROFESSIONAL AND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

A Fir 18 ins. diam. bears N10°W 115.6 ft. dist. marked, T1S R36E S33BT
All distances taken to a brass washer in the blaze of each tree.
Set a steel fence post approx. 6 ft. west of corner with Forest Boundry sign attatched.

Used a steel tape & magnetic compass with declination equal 20° East.

Office of		 Cou	nty of			
State of			-			
for record on the	day of	 ••••••	; 19	, at o	clockn	., (signed)
***************************************		bv				
	NTY OFFICIAL			(DEPUTY		•

Form R6-7100-57 (9/66)

UNION COUNTY SURVEYOR	
Data Received	_

File No. 223 - 84 R

n-to Filed