

T2S36 E09

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

A pine, 14 ins. diam., bears N. 58° W., 26 lks.
dist., with scribe marks S8 visible on partially
healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 2 S R 36 E
S 8 | S 9
S 17 | S 16
1975

from which a new bearing tree

A fir, 6 ins. diam., bears S. 66¾° E., 21½ lks.
dist., mkd. T2S R36E S16 BT.

The cor. of secs. 4, 5, 8, and 9, monumented with a
basalt stone, 18 x 12 x 12 ins., firmly set in a mound of
stone, 3 ft. base, 2 ft. high, mkd. with 5 grooves on S.
and 4 grooves on E. faces, from which the remains of the
original bearing trees:

A pine, 17 ins. diam., bears N. 80° E., 54 lks.
dist., with healed blaze. (Record, N. 75° E.)

A decayed pine stump, 9 ins. diam., bears S. 56½° E.,
49 lks. dist., no marks visible. (Record,
S. 59° E., 46 lks.)

A pine stump, 14 ins. diam., bears S. 42° W., 90 lks.
dist., with scribe marks BT visible on open
blaze.

A pine, 22 ins. diam., bears N. 63° W., 67 lks.
dist., with scribe marks T2S R36E S5 visible on
opened blaze. (Record, N. 65° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins.
in the ground, to solid rock, and in a mound of stone,
6 ft. base, to top, with brass cap mkd.

T 2 S R 36 E
S 5 | S 4
S 8 | S 9
1975

from which new bearing trees

A fir, 8 ins. diam., bears S. 28¾° E., 67 lks.
dist., mkd. T2S R36E S9 BT.

A pine, 8 ins. diam., bears S. 72½° W., 73 lks.
dist., mkd. T2S R36E S8 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a
basalt stone, 15 x 12 x 10 ins., loosely set in a mound of
stone, 3 ft. base, 2 ft. high, no marks visible, from
which the remains of the original bearing trees:

T2S36 E09

T2S36 C09

**UNION COUNTY
SURVEYOR**

Date Received 3/15/13

Date Filed 3/15/13

By MKL Deputy

File No. 3B1-3013R