

T2S36E15

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, with brass cap mkd.

T 2 S R 36 E
¼
S 9 | S 10
1975

from which a new bearing tree

A pine, 19 ins. diam., bears N. 47½° W., 92 lks. dist., mkd. ¼ S9 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 3, 4, 9, and 10, determined at record distance from the remains of the original bearing trees:

A western larch, 17 ins. diam., bears N. 60° E., 30 lks. dist., with scribe mark S visible on partially healed blaze.

A western larch, 30 ins. diam., bears S. 71° E., 33 lks. dist., with healed blaze.

A western larch, 30 ins. diam., bears N. 30° W., 78 lks. dist., no marks visible on partially healed blaze. (Record, N. 32° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E
S 4 | S 3
S 9 | S 10
1975

from which a new bearing tree

A fir, 7 ins. diam., bears S. 54° W., 27 lks. dist., mkd. T2S R36E S9 BT.

The ¼ sec. cor. of secs. 3 and 10, monumented with the remains of a fir post, size indeterminate, from which the remains of the original bearing trees:

A root hole, bears S. 62° E., 40 lks. dist., with a down and decayed pine snag alongside, 12 ins. diam., no marks visible.

A decayed western larch snag, 12 ins. diam., bears N. 22° W., 13 lks. dist., with scribe marks BT visible on opened decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E
¼ S 3
S 10
1975

UNION COUNTY
SURVEYOR
Date Received 3/15/13
Date Filed 3/15/13
By [Signature] DEPUTY
File No. 333-2013R

T2S36 E13

T2S36 E15

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A western larch, 10 ins. diam., bears N. 28° E.,
18 lks. dist., mkd. ¼ S3 BT.

A western larch, 14 ins. diam., bears S. 32¼° W.,
21 lks. dist., mkd. ¼ S10 BT.

Deposit fir post remains alongside iron post.

The ¼ sec. cor. of secs. 3 and 4, monumented with a
basalt stone, 15 x 12 x 10 ins., loosely set in a mound
of stone, mkd. ¼ on W. face, from which the remains of
the original bearing trees:

A root hole, bears S. 66° E., 40 lks. dist., with
a down fir snag alongside, 30 ins. diam., with
scribe marks ¼ S BT visible on open and decayed
double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 2 S R 36 E
¼
S 4 | S 3
1975

from which new bearing trees

A pine, 9 ins. diam., bears N. 82¼° E., 7 lks.
dist., mkd. ¼ S3 BT.

A pine, 18 ins. diam., bears S. 49¾° W., 89 lks.
dist., mkd. ¼ S4 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 28, 29, 32, and 33, monumented with a
basalt stone, 15 x 12 x 8 ins., firmly set 6 ins. in a
mound of stone, 2 ft. base, 1½ ft. high, mkd. with 4
grooves on E. and 1 groove on S. faces, from which the
remains of the original bearing trees:

A pine, 22 ins. diam., bears S. 73° W., 146 lks.
dist., with scribe marks R36E S32 visible on
opened blaze.

A pine, 28 ins. diam., bears N. 70° W., 154 lks.
dist., with healed blaze. (Record, 152 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.
in the ground, and in a mound of stone, 4½ ft. base, to
top, with brass cap mkd.

T 2 S R 36 E
S 29 | S 28
S 32 | S 33
1975

from which new bearing trees

UNION COUNTY SURVEYOR	
Date Received	3/15/13
Date Filed	3/15/13
By	<i>[Signature]</i> Deputy
File No.	538-2013R