


Index File No. J-1

History of original corner establishment:

In 1874, J. Hurlburt, under Contract No. 201 set a Pine post 4 ft. long, 4 ins square on summit of high ridge running from NW to SE, 2 ft. in the ground for Cor. to Sec. 7-8-12 and 13.
Fir 24 in. dia. N 30° W 9 lks.
Pine 48 in. dia. N 53° E 20 lks.
Pine 6 in. dia. S 7° E 40 lks.
Fir 36 in. dia. S 43° W 96 lks. June 13, 1974



Remonumentation by BLM, 1975

The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., determined at record bearing and distnce from the remains of the original bearing trees:

A pine, 40 ins. diam., bears N. 53° E., 20 lks. dist., with scribe marks R6 S visible on partially healed blaze.

A pine, 17 ins. diam., bears S. 7° E., 40 lks. dist., with illegible scribe marks visible on partially healed blaze.

Description of corner evidence found:


FOUND: 2 1/2" Iron Pipe with BLM brass cap set 20" in the ground stamped:

From which:

A 50" dia. Ponderosa Pine dead with open blaze and visible scribing "T2S R 6 S" bears N 53°E 13.3 ft.

An 18" dia. Ponderosa Pine alive with open blaze and visible scribing "36E S" bears S 7° E 26.0 ft.

A 45" Ponderosa Pine (dying) with open blaze and visible scribing "2S R36E S13 B" bears S43°W 64.0 ft.



Original NW BT not found.

An 8" dia. Lodgepole Pine (dead) bears N65°W 50.2 ft. scribed T2S R35E S12 BT (BLM 1975)

Description of monument and accessories I established to perpetuate the original location of this corner:

We mark new BT's as follows:

A Douglas Fir 6" diam. bears N33°W 26.6 ft. scribed T2S R35E S12 BT.

A Douglas Fir 14" dia. bears N68°E 43.1 ft. scribed T2S R36E S7 BT.

A Douglas Fir 10" dia. bears S17°W 20.1 ft. scribed T2S R35E S13 Bt.

Attached 54-3 and 54-4 signs to all BT's. Attached brass washers stamped "LS 1099" to all new BT's. Painted blazes and 6" band around new BT's red.

Compass Declination: 18 1/2° East

I hereby certify the above described corner monument and/or accessories was established as described on June 23, 1981.

Witnesses: Glen Wagoner Loren Huntsman



Office of... Surveyor... County of... Union...

State of... Oregon... I hereby certify that the within instrument was filed in this office

for record on the... 4... day of... OCTOBER... 1982

Howard L. Perry by Gary L. Langlitz (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR stamp with fields for Date Received, Date Filed, By, and File No. 247-84 R

History of original corner establishment:
(Continued)

A pine, 35 ins. diam. bears S 43° W., 96 lks. dist., with scribe marks
2S R35E S13 visible on partially healed blaze. (Record, fir) A root hole, bears
N 30° W., 9 lks. dist., with a down and decayed fir snag alongside, 18 ins. diam.,
no marks visible.

At the corner point set an iron post, 28 ins. long, 2 1/2 ins.
diam., 24 ins. in the ground, with brass cap marked:
from which a new bearing tree, a pine 10 ins. diam., bears N.65° W.
76 lks. dist., mks. T2S R35E S12 BT.

T 2 S
R 35 E R 36 E

from which a new bearing tree.

S 12 | S 7
S 13 | S 18

A Pine, 10 ins. diam., bears N65°W, 76 lks. dist.,
marked T2S R35E S12 BT.

1975

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the
original location of this corner:

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Filed	_____
By	_____
File No.	247-84R

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S
R 35 E R 36 E
S 25 S 30
S 36 S 31
1975

from which new bearing trees

- A pine, 8 ins. diam., bears N. 72½° E., 81 lks. dist., mkd. T2S R36E S30 BT.
- A pine, 10 ins. diam., bears S. 71½° E., 50 lks. dist., mkd. T2S R36E S31 BT.
- A pine, 5 ins. diam., bears S. 55½° W., 109 lks. dist., mkd. BT.
- A pine, 18 ins. diam., bears N. 28½° W., 81½ lks. dist., mkd. T2S R35E S25 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., determined at record distance from the original bearing trees:

- A fir, 24 ins. diam., bears S. 43° E., 12 lks. dist., with scribe marks ¼ S visible on partially healed blaze.
- A pine, 24 ins. diam., bears N. 37° W., 31 lks. dist., with scribe marks ¼ S visible on opened blaze. (Record, N. 32° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S
R 35 E R 36 E
S 25 S 30
1975

The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

- A pine, 40 ins. diam., bears N. 53° E., 20 lks. dist., with scribe marks R6 S visible on partially healed blaze.
- A pine, 17 ins. diam., bears S. 7° E., 40 lks. dist., with illegible scribe marks visible on partially healed blaze.
- A pine, 35 ins. diam., bears S. 43° W., 96 lks. dist., with scribe marks 2S R35E S13 visible on partially healed blaze. (Record, fir)

UNION COUNTY SURVEYOR

Date Received 3/15/12

Date Filed 3/15/13

By J. B. & L. DeWitt

File No. 336-20132

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 30° W., 9 lks. dist., with
a down and decayed fir snag alongside, 18 ins.
diam., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 2 S	
R 35 E	R 36 E
S 12	S 7
S 13	S 18
1975	

from which a new bearing tree

A pine, 10 ins. diam., bears N. 65° W., 76 lks.
dist., mkd. T2S R35E S12 BT.

Subdivision, T. 2 S., R. 36 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by John A. Humlbert,
Deputy Surveyor, in 1874)

The cor. of secs. 25, 26, 35, and 36, monumented with a
basalt stone, 15 x 12 x 9 ins., (record, 12 x 10 x 8 ins.
unmarked) firmly set 8 ins. in the ground, mkd. with 1
groove on E. face, from which the remains of the original
bearing trees:

A root hole, bears N. 40° E., 49 lks. dist.

A root hole, bears S. 10° E., 49 lks. dist.

A fir, 27 ins. diam., bears S. 20° W., 42 lks.
dist., with scribe marks R36 S35 visible on
partially healed blaze.

A root hole, bears N. 65° W., 56 lks. dist.

and bearing trees of no record

A fir, 24 ins. diam., bears N. 57½° E., 51½ lks.
dist., mkd. T2S R36E S25 BT.

A fir, 18 ins. diam., bears S. 36° E., 81 lks.
dist., mkd. T2S R36E S36 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 2 S	R 36 E
S 26	S 25
S 35	S 36
1975	

from which a new bearing tree

A fir, 6 ins. diam., bears N. 28¾° W., 19 lks.
dist., mkd. T2S R36E S26 BT.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

J. L. DEPOY

File No.

336-2013R