

Remonumentation of Certain Original Corner Points,  
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

A pine, 27 ins. diam., bears N.  $31\frac{1}{2}^{\circ}$  W., 104 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

Deposit corner stone alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears S.  $27^{\circ}$  W., 41 lks. dist., with a down and decayed western larch stump alongside, 12 ins. diam., no marks visible.

A root hole, bears N.  $31^{\circ}$  W., 81 lks. dist., with a down and decayed western larch snag alongside, 18 ins. diam., with scribe marks BT visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E  
 $\frac{1}{4}$  S 18  
S 19  
1975

from which new bearing trees

A pine, 10 ins. diam., bears N.  $64\frac{1}{2}^{\circ}$  E.,  $61\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

A fir, 12 ins. diam., bears S.  $15^{\circ}$  W., 35 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

(Remonumenting corners established by Manius Buchanan, Deputy Surveyor, in 1895)

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, determined at record distance from the original bearing trees:

A pine, 11 ins. diam., bears S.  $86^{\circ}$  E., 32 lks. dist., with healed blaze. (Record, S.  $81^{\circ}$  E.)

A pine, 11 ins. diam., bears N.  $54^{\circ}$  W.,  $32\frac{1}{2}$  lks. dist., with scribe marks  $\frac{1}{4}$  E BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E  
 $\frac{1}{4}$  S 18  
S 17  
1975

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 17, determined at record bearing and distance from the remains of the original bearing trees:

UNION COUNTY  
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By J. A. L. DEPUTY

File No. 337-2013P

Remonumentation of Certain Original Corner Points,  
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

A pine, 25 ins. diam., bears N. 34° E., 27 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E  
¼ S 8  
S 17  
1975

from which a new bearing tree

A fir, 10 ins. diam., bears S. 11½° W., 24 lks. dist., mkd. ¼ S17 BT.

The ¼ sec. cor. of secs. 5 and 8, determined at record distance from the remains of the original bearing trees:

A pine, 15 ins. diam., bears N. 63½° E., 12 lks. dist., with scribe marks ¼ S visible on opened blaze.

A fir snag, 12 ins. diam., bears S. 11° E., 27 lks. dist., with scribe marks ¼ S BT visible on partially healed blaze. (Record, S. 71° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E  
¼ S 5  
S 8  
1975

from which a new bearing tree

A pine, 13 ins. diam., bears S. 79½° W., 51 lks. dist., mkd. ¼ S8 BT.

<p><b>UNION COUNTY SURVEYOR</b></p>	
Date Received	<u>3/15/13</u>
Date Filed	<u>3/15/13</u>
By	<u>J. H. L. DEPUTY</u>
File No.	<u>337-20132</u>