

T2S36 N05

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 17, 18, 19, and 20, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 31° E., 11 lks. dist.

A root hole, bears S. 40° E., 30 lks. dist.

A root hole, bears S. 55° W., 6 lks. dist., with a down and decayed western larch snag alongside, 18 ins. diam., no marks visible.

A root hole, bears N. 63° W., 23 lks. dist., with a down and decayed western larch snag alongside, 20 ins. diam., with scribe marks T2S R36E S18 BT visible on decayed double blaze.*

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E
S 18 | S 17
S 19 | S 20
1975

from which new bearing trees

A fir, 8 ins. diam., bears N. 31° E., 11 lks. dist., mkd. T2S R36E S17 BT.

A white fir, 20 ins. diam., bears S. 9¾° E., 30 lks. dist., mkd. T2S R36E S20 BT.

A white fir, 18 ins. diam., bears S. 39½° W., 55½ lks. dist., mkd. T2S R36E S19 BT.

A spruce, 7 ins. diam., bears N. 18½° W., 67 lks. dist., mkd. T2S R36E S18 BT.

T2S36 N05

The ¼ sec. cor. of secs. 17 and 20, monumented with a basalt stone, 18 x 8 x 8 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2½ ft. base, 1½ ft. high, no marks visible, from which the remains of the original bearing trees:

A root hole, bears S. 71° E., 172 lks. dist., with a down and decayed pine snag alongside, 20 ins. diam., no marks visible. (Record, 165 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 36 E
¼ S 17
S 20
1975

from which new bearing trees

A pine, 10 ins. diam., bears S. 42½° E., 118 lks. dist., mkd. ¼ S20 BT.

T2S36 N07

UNION COUNTY SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 343-2013R