

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 17, 18, 19, and 20, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 31° E., 11 lks. dist.

A root hole, bears S. 40° E., 30 lks. dist.

A root hole, bears S. 55° W., 6 lks. dist., with a down and decayed western larch snag alongside, 18 ins. diam., no marks visible.

A root hole, bears N. 63° W., 23 lks. dist., with a down and decayed western larch snag alongside, 20 ins. diam., with scribe marks T2S R36E S18 BT visible on decayed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E
S 18 | S 17
S 19 | S 20
1975

from which new bearing trees

A fir, 8 ins. diam., bears N. 31° E., 11 lks. dist., mkd. T2S R36E S17 BT.

A white fir, 20 ins. diam., bears S. 9¾° E., 30 lks. dist., mkd. T2S R36E S20 BT.

A white fir, 18 ins. diam., bears S. 39½° W., 55½ lks. dist., mkd. T2S R36E S19 BT.

A spruce, 7 ins. diam., bears N. 18½° W., 67 lks. dist., mkd. T2S R36E S18 BT.

The ¼ sec. cor. of secs. 17 and 20, monumented with a basalt stone, 18 x 8 x 8 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2½ ft. base, 1½ ft. high, no marks visible, from which the remains of the original bearing trees:

A root hole, bears S. 71° E., 172 lks. dist., with a down and decayed pine snag alongside, 20 ins. diam., no marks visible. (Record, 165 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S R 36 E
¼ S 17
S 20
1975

from which new bearing trees

A pine, 10 ins. diam., bears S. 42½° E., 118 lks. dist., mkd. ¼ S20 BT.

**UNION COUNTY
SURVEYOR**

Date Received 3/15/13

Date Filed 3/15/13

By J. L. DEPUTY

File No. 344-2013R

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

A pine, 27 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ W., 104 lks.
dist., mkd. $\frac{1}{4}$ S17 BT.

Deposit corner stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears S. 27° W., 41 lks. dist., with a down and decayed western larch stump alongside, 12 ins. diam., no marks visible.

A root hole, bears N. 31° W., 81 lks. dist., with a down and decayed western larch snag alongside, 18 ins. diam., with scribe marks BT visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E
 $\frac{1}{4}$ S 18
S 19
1975

from which new bearing trees

A pine, 10 ins. diam., bears N. $64\frac{1}{2}^{\circ}$ E., 61 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S18 BT.

A fir, 12 ins. diam., bears S. 15° W., 35 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

(Remonumenting corners established by Manius Buchanan, Deputy Surveyor, in 1895)

The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, determined at record distance from the original bearing trees:

A pine, 11 ins. diam., bears S. 86° E., 32 lks. dist., with healed blaze. (Record, S. 81° E.)

A pine, 11 ins. diam., bears N. 54° W., 32 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S R 36 E
 $\frac{1}{2}$ S 18 | S 17
1975

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, determined at record bearing and distance from the remains of the original bearing trees:

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 344-2013R