

100-699

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


99

N-17

History of original corner establishment:

Original survey by General Land Office contract survey;

The original notes state; Set a pine post from which  
A pine 15" in diam. bears N47°W 286 lks dist marked  
T2S R36E S15BT;  
A pine 10" in diam bears S66°E 254 lks dist marked  
T2S R36E S23BT;  
A pine 18" in diam bears N50°E 160 lks dist marked  
T2S R36E S14BT;



Description of corner evidence found:

At N47°W found a down log.  
At N50°E found a pine snag with faint scribe visible.

REGISTERED  
OREGON  
LAND SURVEYOR


*James G. Voelz*

MAY 4, 1956  
JAMES G. VOELZ  
381

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a two inch galvanized pipe 30" long with cap on top and a 8" plated welded to bottom. The pipe set to a depth of approx. 8" and back filled with stone and tamped soil and raised a stone monument.

I stamped the disk



From the monument the new bearing trees are;  
A pine 20" in diam bears N35°E 155lks dist marked  
T2S R36E S14BT;  
A pine 10" in diam bears S68°E 168 lks dist marked T2S R36E  
S23BT;  
A pine 22" in diam bears S57°W 306 lks dist marked T2S R36E S22BT;  
A pine 13" in diam bears N46°W 267 lks dist marked T2S R36E S15BT;  
Distance measured to center of respective trees and marked with a scribe.  
I set a steel fence post with USFS sign 54-4 attached. USFS bearing tree signs were placed on the bearing trees facing the corner shoulder high.

Office of.....County.....surveyor..... County of..... Union

State of.....Oregon....., I hereby certify that the within instrument was filed in this UNION COUNTY SURVEYOR  
for record on the 22 day of Oct. 1969, at 9 o'clock P.M., (signed)  
..... county surveyor by *James G. Voelz*  
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received.....

Date Filed.....

By.....

File No. 277-84 R.