

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 19, 20, 29, and 30, monumented with a basalt stone, 18 x 12 x 10 ins., firmly set 10 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A decayed fir stump, 18 ins. diam., bears N. 38° E., 21 lks. dist., no marks visible.

A pine, 18 ins. diam., bears S. 84° E., 81 lks. dist., with scribe marks T2S 36E S29 visible on partially healed blaze.

A pine, 25 ins. diam., bears S. 3° W., 21 lks. dist., with illegible scribe marks visible on partially healed blaze.

A root hole, bears N. 62° W., 40 lks. dist., with a down and decayed pine snag alongside, 24 ins. diam., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a mound of stone, with brass cap mkd.

T 2 S R 36 E
S 19 | S 20
S 30 | S 29
1975

from which new bearing trees

A pine, 10 ins. diam., bears N. 48° E., 19 lks. dist., mkd. T2S R36E S20 BT.

A pine, 10 ins. diam., bears N. 46½° W., 44 lks. dist., mkd. T2S R36E S19 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 19 and 20, monumented with a basalt stone, 15 x 14 x 12 ins., firmly set 10 ins. in a mound of stone, 3 ft. base, 1½ ft. high, no marks visible, from which the remains of the original bearing trees:

A pine, 16 ins. diam., bears N. 63½° E., 42 lks. dist., with scribe marks BT visible on opened blaze. (Record, N. 60° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.

T 2 S R 36 E
¼
S 19 | S 20
1975

from which a new bearing tree

A pine, 18 ins. diam., bears N. 12½° W., 70 lks. dist., mkd. ¼ S19 BT.

Deposit corner stone alongside iron post.

UNION COUNTY SURVEYOR	
Date Received	<u>3/15/13</u>
Date Filed	<u>3/15/13</u>
By	<u>J. J. L. DEPUTY</u>
File No.	<u>345-2013R</u>