


6

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by General Land Office contract survey,  
The original notes state;  
Set post from which  
Pine 12" dia bears N74°W 100 lks. marked †SBT;  
Fir 15" dia. bears S29°E 147 lks. marked †SBT;



Description of corner evidence found:

In section 20, found a Yellow pine 22" in diam, and in good shape and living.


Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 30" galvanized pipe with an eight inch plate welded to bottom and a bronze cap on top. The hole dug to a depth of eight inches and backfilled and raised a stone monument.

I stamped the disk

From the monument the original bearing trees was;  
Yellow pine 22" in diam bears N74°W 100 lks.  
I established the following new bearing tree;  
Ponderosa pine 15" in diam bears S15°E at a distance of 32 ft.  
and scribed †SBT.

The distance measured to center of respective trees on level. I placed bearing tree signs on both old and new bearing trees and painted stripe around the trees. I placed a steel fence post with USFS sign 54-4 attached.



Office of County Surveyor County of Union  
State of Oreg., I hereby certify that the within instrument was filed in this office  
for record on the 28 day of AUGUST, 1970, at 4 o'clock P.m., (approved)  
County surveyor by Deputy  
(COUNTY OFFICIAL) (DEPUTY)

<b>UNION COUNTY SURVEYOR</b>
Date Received _____
Date Filed _____
By _____
File No. <u>287-84R</u>