


Index File No. R-9

History of original corner establishment:

In 1874, John A Hurlburt, under GLO contract No. 201, set a basalt stone 15x12x12 8 inches in the ground for Cor. to Sec. 20, 21, 27, 28. BT's: Pine 24" in dia. bears N45° W 69 lks. Pine 18" in dia. bears N 63° E 84 lks.; Pine 24" in dia. bears S 33° E 67 lks.; Pine 18" in dia. bears S 21°W 87 lks.



Remonumentation by Bureau of Land Management, 1975:

The cor. of secs. 20, 21, 28, and 29, monumented with a basalt stone, 15x12x12 ins., firmly set 8 ins. in the ground, marked with 4 grooves on E. face, from which the remains of the original bearing trees: A decayed pine stump, 18 ins. diam., bears N. 63° E., 84 lks. dist., no marks visible.

A decayed pine snag, 25 ins. diam., bears S. 33° E., 67 lks. dist., with scribe marks T2S R36E S28 visible on open blaze. (cont'd. on next page)

Description of corner evidence found:

FOUND: 2 1/2" Iron Pipe with cap set 18" in ground stamped: Bureau of Land Management T2S R36E

Original BT's: A 10" tall Pine snag, 25" dia. bears S 33° E 44.2 scribing T2S R3 S28 visible.

S20 S21

A 28" Pine S21 W 57.5 ft. in good condition with visible scribing 2 R36E S29°

S29 S28

A Pine stump 22" bears N 43°W 45.4 ft. No visible scribing. The original N.E. BT is gone.

1975

BLM BT's 1975:

A 14" pine bears N 54° W 13.7 ft. with visible scribing T2S R36E S20 BT.

A 6" D. Fir bears N68°W 4.0 ft. with visible scribing T2S R36E S21 BT. A P. Pine dead 12" in dia. bears S53°E 26.4 ft. with scribing T2S R36E S28 BT visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

We mark a new BT as follows:


An 8" D. Fir bears S22° E 24.3 ft. scribed T2S R36E S20 BT.

Attached brass washer with PLS1099 and attached all signs and painted BT's per Standard Specification for Cadastral Survey, USFS Region 6, October, 1979.

Compass Declination: 18 1/2° East

I hereby certify the above described corner monument and/or accessories was established on June 30, 1981.

Witnesses: Loren Huntsman Millard Wyatt



Surveyor \_\_\_\_\_ Union \_\_\_\_\_  
 Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of Oregon \_\_\_\_\_, I hereby certify that the within instrument was filed in this office  
 for record on the 4 day of OCTOBER 1982  
 Howard L. Perry \_\_\_\_\_ by Gary L. Langlitz \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY SURVEYOR**

Date Received \_\_\_\_\_  
 Date Filed GPO 799-509 \_\_\_\_\_  
 By \_\_\_\_\_  
 File No. 300-84R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: (Cont'd)

A pine, 28 ins. diam., bears S. 21° W., 87 lks. dist., with scribe marks 36E 29 visible on partially healed blaze.

A pine stump, 22 ins. diam., bears N. 45° W., 69 lks. dist., no marks visible. At the corner point set an iron post, 28 ins. long, 2 1/2 ins. diam. 24" in the ground, with brass cap mkd.

T 2 S R 36 E  
S20 | S21  
S29 | S28  
1975

from which new bearing trees, A fir, 6 ins. diam., bears N. 68 3/4° E., 6 lks. dist., mkd. T2S R36E S21 BT.

A pine, 12 ins. dia., bears S53 1/4° E., 40 lks. dist., mkd. T2S R36E S28 BT.

A pine, 14 ins. diam., bears N. 54° W. 21 lks. diam. mkd. T2S R36E S20 BT. Deposit corner stone alongside iron post.

Description of corner evidence found:

Description of monument and accessories | established to perpetuate the original location of this corner:

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....  
..... by .....

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received \_\_\_\_\_

GPO 799-509

Date Filed \_\_\_\_\_

By \_\_\_\_\_

File No. 300-84 R

Remonumentation of Certain Original Corner Points,  
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

~~A pine, 10 ins. diam., bears N. 73½° E., 396 lks.  
dist., mkd. T2S R36E S28 BT.~~

~~A pine, 17 ins. diam., bears S. 44½° E., 165 lks.  
dist., mkd. T2S R36E S33 BT.~~

~~Deposit corner stone alongside iron post.~~

The cor. of secs. 20, 21, 28, and 29, monumented with a  
basalt stone, 15 x 12 x 12 ins., firmly set 8 ins. in the  
ground, mkd. with 4 grooves on E. face, from which the  
remains of the original bearing trees:

A decayed pine stump, 18 ins. diam., bears  
N. 63° E., 84 lks. dist., no marks visible.

A decayed pine snag, 25 ins. diam., bears S. 33° E.,  
67 lks. dist., with scribe marks T2S R36E S28  
visible on open blaze.

A pine, 28 ins. diam., bears S. 21° W., 87 lks.  
dist., with scribe marks 36E 29 visible on  
partially healed blaze.

A pine stump, 22 ins. diam., bears N. 45° W., 69  
lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 2 S R 36 E  
S 20 | S 21  
S 29 | S 28  
1975

from which new bearing trees

A fir, 6 ins. diam., bears N. 68¾° E., 6 lks.  
dist., mkd. T2S R36E S21 BT.

A pine, 12 ins. diam., bears S. 53¼° E., 40 lks.  
dist., mkd. T2S R36E S28 BT.

A pine, 14 ins. diam., bears N. 54° W., 21 lks.  
dist., mkd. T2S R36E S20 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 8, 9, 16, and 17, determined at record  
bearing and distance from the remains of the original  
bearing trees:

~~A fir, 30 ins. diam., bears N. 53° E., 40 lks.  
dist., with illegible scribe marks visible on  
partially healed blaze.~~

~~A root hole, bears S. 67° E., 55 lks. dist., with  
a down and decayed pine snag alongside, 30 ins.  
diam., with axe marks visible.~~

~~A fir, 25 ins. diam., bears S. 78° W., 92 lks.  
dist., no marks visible on partially healed  
double blaze.~~

**UNION COUNTY  
SURVEYOR**

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 349-2013R