

Remonumentation of Certain Original Corner Points,
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 2 S
R 35 E R 36 E
S 25 S 30
S 36 S 31
1975

from which new bearing trees

A pine, 8 ins. diam., bears N. 72½° E., 31 lks. dist., mkd. T2S R36E S30 BT.

A pine, 10 ins. diam., bears S. 71½° E., 50 lks. dist., mkd. T2S R36E S31 BT.

A pine, 5 ins. diam., bears S. 55½° W., 109 lks. dist., mkd. X BT.

A pine, 18 ins. diam., bears N. 28½° W., 81½ lks. dist., mkd. T2S R35E S25 BT.

Deposit corner stone alongside iron post.

The ½ sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., determined at record distance from the original bearing trees:

A fir, 24 ins. diam., bears S. 43° E., 12 lks. dist., with scribe marks ½ S visible on partially healed blaze.

A pine, 24 ins. diam., bears N. 37° W., 31 lks. dist., with scribe marks ½ S visible on opened blaze. (Record, N. 32° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 S
R 35 E R 36 E
S 25 S 30
1975

The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A pine, 40 ins. diam., bears N. 53° E., 20 lks. dist., with scribe marks R6 S visible on partially healed blaze.

A pine, 17 ins. diam., bears S. 7° E., 40 lks. dist., with illegible scribe marks visible on partially healed blaze.

A pine, 35 ins. diam., bears S. 43° W., 46 lks. dist., with scribe marks 2S R35E S13 visible on partially healed blaze. (Record, fir)

T2S 36 T01

UNION COUNTY SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] Deputy

File No. 350-2013R