


Index File No. V 5  
T 2S R. 36E  
Merid. \_\_\_\_\_ N.F. \_\_\_\_\_

**CORNER RECORD (SEARCH)**  
(Ref. FSM 7151.4)

Tract or Survey No. \_\_\_\_\_  
County \_\_\_\_\_  
State \_\_\_\_\_

Cor. No. \_\_\_\_\_

**CORNER DIAGRAM**



**DESCRIBE CORNER MONUMENT FOUND**

The corner to sections 29, 30, 31 & 32 monumented with a basalt stone 14" x 10" x 6" firmly set 6" in the ground and in a mound of stones 2' base 1 1/2' high with 5 grooves on E. face from which the original bearing trees

**DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND**

A pine 28" dia. bears N. 32 E. 85 lks. with scribe marks 6 2 visible in partially healed blaze  
A pine 18" dia. bears N. 68 W. 46 lks. with scribe marks 2S R36E S visible in partially healed blaze (record N. 64 W. )

**PHOTO IDENTIFICATION DATA**

Photo No. ENW 4-153  
Filed At. \_\_\_\_\_  
Object Ident. \_\_\_\_\_  
Ident. By \_\_\_\_\_  
*Signature*

**DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER**

**PLANE COORDINATE POSITION DATA**


State \_\_\_\_\_ Zone \_\_\_\_\_  
X \_\_\_\_\_  
Y \_\_\_\_\_  
Estab. By \_\_\_\_\_  
*Agency*

Signature \_\_\_\_\_ Title \_\_\_\_\_ Division \_\_\_\_\_ Headquarters \_\_\_\_\_ Date 7100-52 (3/68)

**CORNER RECORD (PERPETUATION)**

**MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT**

Set an iron post 28" long 2 1/2" dia. 12" in the ground to solid rock and in a mound of stones 4' base to top with brass cap marked



**ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE**

A pine 17" dia. bears S. 19 E 299 lks. marked T2S R36E S32 BT  
A pine 20" dia. bears S. 84 W. 234 lks. marked T2S R36E S31 BT

Work Done By Garrison Title C Surveyor Date 7/75 State Registration No. or Agency \_\_\_\_\_  
Certified Cor. Record Prepared? Yes  No  Filed At: \_\_\_\_\_ Date \_\_\_\_\_

**REMARKS**

Index File No. \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Tract or Surv. No. \_\_\_\_\_ Cor. \_\_\_\_\_

**UNION COUNTY SURVEYOR**  
Date Received \_\_\_\_\_  
Date Filed 12-16-87  
By G. LANGLITZ, DEPUTY  
File No. 193-87R

V-5

Remonumentation of Certain Original Corner Points,  
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 83° E., 76 lks. dist., with  
a down and decayed pine snag alongside, 30 ins.  
diam., no marks visible.

A sawed and decayed pine stump, 30 ins. diam.,  
bears S. 32° W., 91 lks. dist., with scribe mark  
T visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.  
in the ground, in a mound of stone, 5 ft. base, to top,  
with brass cap mkd.

T 2 S R 36 E  
    ½  
S 5 | S 4  
    1975

from which new bearing trees

A pine, 20 ins. diam., bears N. 50° E., 106 lks.  
dist., mkd. ½ S4 BT.

A pine, 15 ins. diam., bears N. 62½° W., 64 lks.  
dist., mkd. ½ S5 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 29, 30, 31, and 32, monumented with a  
basalt stone, 14 x 10 x 6 ins., firmly set 6 ins. in the  
ground, and in a mound of stone, 2 ft. base, 1½ ft. high,  
mkd. with 5 grooves on E. face, from which the original  
bearing trees:

A pine, 28 ins. diam., bears N. 32° E., 85 lks.  
dist., with scribe marks 6 2 visible on partially  
healed blaze.

A pine, 18 ins. diam., bears N. 68° W., 46 lks.  
dist., with scribe marks 2S R36E S visible on  
partially healed blaze. (Record, N. 64° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.  
in the ground, to solid rock, and in a mound of stone,  
4 ft. base, to top, with brass cap mkd.

T 2 S R 36 E  
    S 30 | S 29  
    S 31 | S 32  
    1975

from which new bearing trees

A pine, 17 ins. diam., bears S. 19° E., 299 lks.  
dist., mkd. T2S R36E S32 BT.

A pine, 20 ins. diam., bears S. 84° W., 234 lks.  
dist., mkd. T2S R36E S31 BT.

Deposit corner stone alongside iron post.

UNION COUNTY  
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 353-2013R