


Index File No. V 9 CORNER RECORD (SEARCH) Tract or Survey No. \_\_\_\_\_ Cor. No. \_\_\_\_\_  
 T 25 R. 36E R.D. \_\_\_\_\_ County \_\_\_\_\_  
 Merid. \_\_\_\_\_ N.F. \_\_\_\_\_ State \_\_\_\_\_

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

The corner to sections 28, 29, 32 & 33 monumented with a basalt Stone 15" x 12" x 8" firmly set 6" in the ground and in a mound of stone 2' base and 1 1/2' high marked with 4 grooves on E. face and 1 groove on the S. face from which the remains of the original bearing trees

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

A pine 22" dia. bears S. 73° W. 146 lks. with scribe marks R36E S32 visable in open blaze  
 A pine 28" dia. bears N. 70° W. 154 lks. with healed blaze

PHOTO IDENTIFICATION DATA

Photo No. \_\_\_\_\_  
 Filed At. \_\_\_\_\_  
 Object Ident. \_\_\_\_\_  
 Ident. By \_\_\_\_\_  
*Signature*

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

PLANE COORDINATE POSITION DATA


State \_\_\_\_\_ Zone \_\_\_\_\_  
 X \_\_\_\_\_  
 Y \_\_\_\_\_  
 Estab. By \_\_\_\_\_  
*Agency*

Signature \_\_\_\_\_ Title \_\_\_\_\_ Division \_\_\_\_\_ Headquarters \_\_\_\_\_ Date \_\_\_\_\_ 7100-52  
 REV. 65 5

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set an iron post 29" llong 2 1/2" dia. 10" in the ground and in a mound of stone 4 1/2' base to top with brass cap marked:



ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

New Bearing Trees

A pine 10" dia. bears N. 73 1/2° E. 396 lks marked T2S R36E S28 BT  
 A pine 17" dia. bears S. 44 3/4° E. 165 lks. marked T2S R36E S33 BT  
 Deposit corner stone along side iron post

Work Done By Garrison Title C. Surveyor Date 7/75 State Registration No. \_\_\_\_\_ or Agency \_\_\_\_\_  
 Certified Cor. Record Prepared? Yes \_\_\_\_\_ No \_\_\_\_\_ Filed At: \_\_\_\_\_ Date \_\_\_\_\_

REMARKS

Index File No. \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Tract or Surv. No. \_\_\_\_\_ Cor. No. \_\_\_\_\_

**UNION COUNTY SURVEYOR**

Date Received \_\_\_\_\_

Date Filed 12-16-87

By G. LANGLITZ, DEPUTY

File No. 194-87R

V-9

T2S 36E 69

423

Remonumentation of Certain Original Corner Points,  
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A western larch, 10 ins. diam., bears N. 28° E.,  
18 lks. dist., mkd. ¼ S3 BT.

A western larch, 14 ins. diam., bears S. 32¾° W.,  
21 lks. dist., mkd. ¼ S10 BT.

Deposit fir post remains alongside iron post.

---

The ¼ sec. cor. of secs. 3 and 4, monumented with a  
basalt stone, 15 x 12 x 10 ins., loosely set in a mound  
of stone, mkd. ¼ on W. face, from which the remains of  
the original bearing trees:

A root hole, bears S. 66° E., 40 lks. dist., with  
a down fir snag alongside, 30 ins. diam., with  
scribe marks ¼ S BT visible on open and decayed  
double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 2 S R 36 E  
S 4 | S 3  
1975

from which new bearing trees

A pine, 9 ins. diam., bears N. 82¾° E., 7 lks.  
dist., mkd. ¼ S3 BT.

A pine, 18 ins. diam., bears S. 49¾° W., 89 lks.  
dist., mkd. ¼ S4 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 28, 29, 32, and 33, monumented with a  
basalt stone, 15 x 12 x 8 ins., firmly set 6 ins. in a  
mound of stone, 2 ft. base, 1½ ft. high, mkd. with 4  
grooves on E. and 1 groove on S. faces, from which the  
remains of the original bearing trees:

A pine, 22 ins. diam., bears S. 73° W., 146 lks.  
dist., with scribe marks R36E S32 visible on  
opened blaze.

A pine, 28 ins. diam., bears N. 70° W., 154 lks.  
dist., with healed blaze. (Record, 152 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.  
in the ground, and in a mound of stone, 4½ ft. base, to  
top, with brass cap mkd.

T 2 S R 36 E  
S 29 | S 28  
S 32 | S 33  
1975

from which new bearing trees

**UNION COUNTY  
SURVEYOR**

Date Received 2/15/13

Date Filed 3/15/13

By J. H. L. DEPT

File No. 354-2013R

Remonumentation of Certain Original Corner Points,  
T. 2 S., R. 36 E., Willamette Meridian, Oregon

CHAINS

A pine, 10 ins. diam., bears N. 73½° E., 396 lks.  
dist., mkd. T2S R36E S28 BT.

A pine, 17 ins. diam., bears S. 44¾° E., 165 lks.  
dist., mkd. T2S R36E S33 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 20, 21, 28, and 29, monumented with a  
basalt stone, 15 x 12 x 12 ins., firmly set 8 ins. in the  
ground, mkd. with 4 grooves on E. face, from which the  
remains of the original bearing trees:

A decayed pine stump, 18 ins. diam., bears  
N. 63° E., 84 lks. dist., no marks visible.

A decayed pine snag, 25 ins. diam., bears S. 33° E.,  
67 lks. dist., with scribe marks T2S R36E S28  
visible on open blaze.

A pine, 28 ins. diam., bears S. 21° W., 87 lks.  
dist., with scribe marks 36E 29° visible on  
partially healed blaze.

A pine stump, 22 ins. diam., bears N. 45° W., 69  
lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 2 S R 36 E  
S 20 | S 21  
S 29 | S 28  
1975

from which new bearing trees

A fir, 6 ins. diam., bears N. 68¾° E., 6 lks.  
dist., mkd. T2S R36E S21 BT.

A pine, 12 ins. diam., bears S. 53½° E., 40 lks.  
dist., mkd. T2S R36E S28 BT.

A pine, 14 ins. diam., bears N. 54° W., 21 lks.  
dist., mkd. T2S R36E S20 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 8, 9, 16, and 17, determined at record  
bearing and distance from the remains of the original  
bearing trees:

A fir, 30 ins. diam., bears N. 53° E., 40 lks.  
dist., with illegible scribe marks visible on  
partially healed blaze.

A root hole, bears S. 67° E., 55 lks. dist., with  
a down and decayed pine snag alongside, 30 ins.  
diam., with axe marks visible.

A fir, 25 ins. diam., bears S. 78° W., 92 lks.  
dist., no marks visible on partially healed  
double blaze.

**UNION COUNTY  
SURVEYOR**

Date Received 3/5/13

Date Filed 3/5/13

By [Signature] DEPUTY

File No. 354-2013R