CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner established by Henry Meldrum under GLO contract no. 450 dated June 11, 1882.

Surveyor General records state:

Set basalt stone 16 x 12 x 5 ins 11 ins in the ground for $\frac{1}{4}$ Sec Cor marked 1/4 on W face from which:

A pine 4 ins diam bears N 72° E, 10 lks dist marked 1/4 S BT. A pine 18 ins diam bears S 88° W, 24 lks dist marked 1/4 S BT.



Description of corner evidence found:

A sawed pine stump 18 ins diam for Section 2 bearing tree marked with BT on remaining blaze.

No trace of Section 1 bearing tree.

Found a stone of record size but failed to identify any chisle work.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a $2\frac{1}{2}$ inch aluminum cap on a 2 inch aluminum pipe 30 inches long 24 inches in the ground with 6 inches projecting out of the ground with a surrounding rock mound and a 6 foot steel fence post alongside with a sign 54-4 attached.

Aluminum cap marked thus:

ORLS 1639

New bearing trees:

A pine 11 ins diam bears S 89° W, 21.7 feet dist marked 1/4 S 2 BT A pine 13 ins diam bears N 47° E, 10.2 feet dist marked 1/4 S 1 BT.

Each new bearing tree has a sign 54-3 attached below a 6 inch band of red paint and a brass washer marked PLS 1639 nailed flush with BT blaze. A sign 54-4 is attached on opposite side of tree from BT blaze.

I hereby certify that the above described corner was properly monumented by me on Sept. 7, 1983, and witnessed by Jim DeMastus.

REGISTERED PROFESSIONAL LAND SURVEYOR

William L. Harley

OREGOM
JULY 14, 1978
WILLIAM L. HANLEY
1639

UNION COUNTY

Form R6-7100-57 (9/71)

Date Filed 9-28-83

By G. LANGUTZ, DEPUT