


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Henry Meldrum under GLO contract no. 450, dated June 11, 1882.

Surveyors General records state:

Set post 4 ft long 4 ins square 24 ins in ground for cor to secs 2, 3, 10 & 11, marked T 2 S S 2 on NE, R 37 E S 3 on NW, S 10 on SW and S 11 on SE with 5 notches on S and 2 on E edges, from which:



- A pine 6 ins diam bears N 60° W, 8 lks dist marked R 37 E S 3 BT.
- A pine 4 ins diam bears N 32° E, 50 lks dist marked T 2 S S 2 BT.
- A pine 15 ins diam bears S 49° E, 15 lks dist marked S 11 BT.
- A pine 5 ins diam bears S 34° W, 14 lks dist marked S 10 BT.

Description of corner evidence found:


Found a dead and standing pine 7 ins diam with record scribes, R 37 E S 3 BT, for section 3 bearing tree.

No trace of other record bearing trees or of original wood post.

Description of monument and accessories established to perpetuate the original location of this corner:

A record position as determined from original section 3 bearing tree and official record notes set a 2½ inch brass cap on a 2 inch galvanized iron pipe 31 inches long and buried to a depth of 25 inches in the ground with 6 inches projecting out of the ground with a surrounding rock mound and a 6 foot steel fence post alongside with a sign 54-4 attached.

Brass cap marked thus:



New bearing trees:

- A fir 8 ins diam bears N 78° E, 32.4 ft dist marked T 2 S R 37 E S 2 BT.
- A pine 15 ins diam bears N 42° W, 7.8 ft dist marked T 2 S R 37 E S 3 BT.
- A fir 17 ins diam bears S 64° W, 21.1 ft dist marked T 2 S R 37 E S 10 BT.
- A pine 17 ins diam bears S 43° E, 19.6 ft dist marked T 2 S R 37 E S 11 BT.

Each new bearing tree has a sign 54-3 nailed below a 6 inch band of red paint and has a brass washer marked PLS 1639 nailed flush with BT blaze and a sign 54-4 nailed on opposite side of tree from BT blaze.

I hereby certify that the above described corner monument was properly established by me on July 12, 1983, and witnessed by Jim DeMastus.

Office of County Surveyor County of Union  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the        day of       , 19    
 by         
 (COUNTY OFFICIAL)

**UNION COUNTY SURVEYOR**  
(DEPUTY)

Date Received 8-15-83  
 Date Filed 8-18-83  
 By G. LANGRISH Deputy  
 File No. 316-83 R

REGISTERED PROFESSIONAL LAND SURVEYOR

*William L. Hanley*

OREGON  
JULY 14, 1978  
WILLIAM L. HANLEY  
1639