
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner not previously established.



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Corner not previously established See map of survey dated November, 1989.

Description of monument and accessories I established to perpetuate the

original location of this corner: At position determined by survey, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 30 inches in the ground, from which:


New Bearing Trees;
A 11 inch diameter Ponderosa Pine bears N14°E, 28.40 feet marked Y BT
A 20 inch diameter Ponderosa Pine bears S41°E, 12.50 feet marked C½ S19 BT
A 8 inch diameter Ponderosa Pine bears S7°W, 18.91 feet marked F BT
A 18 inch diameter Ponderosa Pine bears N48°W, 31.43 feet marked X BT
Painted a 6 inch red band around all BTs and attached
bearing tree and land survey monument signs.

Set a steel feacepost approximately 5 feet North with land survey monument sign attached.

Raised a mound of stone around monument, 3 ft. base to top of cap.

I hereby certify that the above corner point was perpetuated as hereon described on November 11, 1989.

Witnesses: Greg Blackman and Jeff Petersen.



OREGON
JULY 10, 1964

DUANE I. GRIFFITH
644

REGISTERED PROFESSIONAL AND SURVEYOR

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of	County of	
State of	, I hereby certify that the wi	ithin instrument was filed in this office
for record on the	day OKION COUNTY	(DEPUTY)
(COUNTY	OFFICIAL, SURVEYOR	(DEPUTY)
DE 7100 E7 /0/71\		

Form R6-7100-57 (9/71)

Dato Roceived 12-27-89

Dato Filed 12-27-80

By R. ROBINSON, DEPUTY

Ho No. 249 ROR

\$U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276

P~03

2-13