
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Henry Meldrum under GLO Contract Number 450, dated June 11, 1882. Surveyor General record states:

Set post 3 ft. long, 3 in. square, 24 in. in ground for ¼ Sec. Cor. marked ¼ S on W face, from which;

A Fir 6 in. diam. bears S60°E, 22 lks. dist. marked ¼S BT A Tamarack 5 in. diam. bears S47°W, 18 lks. dist. marked ¼S BT



No record of subsequent monumentation found in Union County survey records

Description of corner evidence found:

Found no evidence of the original corner monument.

The area has been very heavily logged.

See map of survey dated June 1992.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the proportionate position as determined by survey, I set a 2½"x30" aluminum pipe with aluminum cap marked as shown, 24 inches in the ground. from which:

New Bearing Trees;
A 8 inch diameter Tamarack bears N48°E, 5.82 feet marked X BT
A 9 inch diameter Tamarack bears S53°E, 36.14 feet marked ½ S21 BT
A 10 inch diameter Ponderosa pine bears S4°E, 57.80 feet marked ½ S21 BT
A 7 inch diameter White fir bears S60°W, 15.91 feet marked X BT

Raised mound of stone 31 base to top of cap.


Set a steel fence post approximately 5 feet North with Attention sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on June 1, 1992.

Witness: Peter Crabtree

REGISTERED
PROFESSIONAL
LAND SURVEYOR

CHOISEN
DUANE I. GRIFFITH
644



I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Form R6-7100-57 (9/71)

9/15/92 Jugar 1. Sterler File No. 062-1992R ☆ GPO:

P-09

1-11